



### Features

- Front I/O interface
- Shock-resistant bay space for 3.5" disk drive
- Cutouts for two COM, one DVI/LVDS, one S/C-video
- Supports AC(250W) Flex ATX power supply
- Reusable and washable air filter
- LED indicators for system power and HDD

### Specifications

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Dimensions   | 10.7 in x 3.5 in x 9.1 in (272 mm x 88 mm x 232 mm) (W x H x D)                 |
| Drive Bays   | One 3.5" HDD internal drive bay                                                 |
| Construction | Heavy-duty steel                                                                |
| Color        | Standard: gray                                                                  |
| Cooling Fans | One 60 mm x 60 mm x 15 mm ball bearing fans                                     |
| Front Panel  | LEDs: HDD activity and system power<br>System reset switch and ATX power switch |
| Power Supply | Supports Flex ATX power supply                                                  |
| Carton Size  | 15.5 in x 14.6 in x 8.5 in (395 mm x 375 mm x 215 mm)                           |
| Weight       | Net 2 kg (4.4 lb)                                                               |

### Power Supply Options

| Model Number | Watt  | Input Range | Output (Max.) |        |       |       |      |        |
|--------------|-------|-------------|---------------|--------|-------|-------|------|--------|
|              |       |             | +5 V          | +3.3 V | +12 V | -12 V | -5 V | +5 Vsb |
| APS-925XU    | 250 W | Universal   | 14 A          | 12 A   | 18 A  | 0.3 A | -    | 2.5 A  |

### Ordering Information

| Model Number | Color | Power Supply |
|--------------|-------|--------------|
| MK-100       | Gray  | -            |
| NS-100MI-250 | Gray  | APS-925XU    |

### Mechanical Layout



### Dimensions

Units: mm

