

NuPRO-820 Series

Half-Size Low Power Consumption Pentium® M ePCI-X SBC with DVI/LVDS/Six SATA ::



Features

- Low power consumption Pentium® M / Celeron® M Processor
- Longevity Intel® 855GME chipset with 6300ESB
- Maximum 2GB DDR 266/333
- 6-CH SATA-150, 4-CH support RAID 0/1, single ATA-100
- VGA, DVI, LVDS, GbE, four USB 2.0, COM, and WDT
- 66MHz/64-bit ePCI-X expansion bus
- Easy customization for OEM programs

Ordering Information

NuPRO-820-P1600/512	PICMG 1.2 Half-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Pentium M 1.6GHz/512MB DDR333
NuPRO-820-C1300/512	PICMG 1.2 Half-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Celeron M 1.3GHz/512MB DDR333
NuPRO-820-P1100/512	PICMG 1.2 Full-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Pentium M 1.1GHz/512MB DDR333

Note: Call for availability of more CPU and memory options

Specifications

CPU / Core Logic

CPU	Pentium M processors, 1.1GHz-2.0GHz Celeron M processors, 600MHz-1.3GHz
FSB	400MHz
Chipset	Intel 855GME chipset, with 6300ESB, FWH
RAM	Two DDR SO-DIMM sockets, supports DDR266/333 up to 2GB
BIOS	Award 4Mb flash memory

Bus

Bus-A	ePCI-X Bus-A complaint with PCI-X 66MHz
-------	---

I/O Interfaces

IDE	ATA-100, single channel
CompactFlash	On board CompactFlash support
Serial ATA	Support 6 channels SATA-150 Two by 6300ESB Four by SiliconImage 3114, support RAID 0/1
USB	2 USB ports on the faceplate, 2 by pin header Compliant with USB Specification Rev. 2.0, individual over-current protection
Super I/O	One RS-232 COM port with ESD protection to 2KV
Audio	Integrated Audio Controllers with AC'97 interface, with optional DB-AC97S daughter board
Watchdog Timer	Built-in 6300ESB, support 2-stage WDT

VGA

Display	Built-in with 855GME. 350MHz integrated 24-bit RAMDAC that can a standard progressive scan analog monitor with pixel resolution up to 1600 x 1200 at 85MHz and 2048 x 1536 at 75MHz. One DVI interface supports up to 165 Mpixels/sec, resolutions up to 1600 x 1200 UXGA display One channel LFP transmitter interface to support LVDS LCD panel resolutions up to UXGA
---------	--

Ethernet

Ethernet	Intel 82541GI Ethernet controller Supports 1000Base-TX, 100Base-TX and 10Base-T (IEEE802.3, 802.3u, and 802.3ab)
Features	Intel PXE pre-boot on Ethernet

Mechanical and Environmental

Form Factor	Standard Half-Size PICMG 1.2 CPU Card PICMG 1.2
Dimension	191mm x 122mm (L x W)
Operating Temp.	0 to 60°C
Storage Temp.	-20 to 80°C
Compliance	CE, FCC Class A

1
AdvancedTCA
Products

2
6U cPCI
SBC

3
6U cPCI
Platforms

4
3U cPCI
SBC

5
3U cPCI
Platforms

6
SBC & IMB

7
Industrial
Chassis

8
ETX &
Embedded
Modules

9
Network
Appliance

10
IPC
Accessories