




ADLINK
TECHNOLOGY INC.

cPCI-3920 Series

**3U CompactPCI Blade with Intel® Core™2 Duo,
Core™ Duo, Celeron® M Processor**

User's Manual



Manual Rev. 2.20
Revision Date: August 30, 2010
Part No: 50-15064-1020



Recycled Paper

Advance Technologies; Automate the World.

Revision History

Revision	Release Date	Description of Change(s)
2.00	2008/07/07	Initial Release
2.10	2008/09/04	Update BIOS chapter
2.20	2010/08/30	Correct pin definitions (SATA0, J2, COM2, rJ2); update BIOS

Preface

Copyright 2010 ADLINK Technology Inc.

This document contains proprietary information protected by copyright. All rights are reserved. No part of this manual may be reproduced by any mechanical, electronic, or other means in any form without prior written permission of the manufacturer.

Disclaimer

The information in this document is subject to change without prior notice in order to improve reliability, design, and function and does not represent a commitment on the part of the manufacturer.

In no event will the manufacturer be liable for direct, indirect, special, incidental, or consequential damages arising out of the use or inability to use the product or documentation, even if advised of the possibility of such damages.

Environmental Responsibility

ADLINK is committed to fulfill its social responsibility to global environmental preservation through compliance with the European Union's Restriction of Hazardous Substances (RoHS) directive and Waste Electrical and Electronic Equipment (WEEE) directive. Environmental protection is a top priority for ADLINK. We have enforced measures to ensure that our products, manufacturing processes, components, and raw materials have as little impact on the environment as possible. When products are at their end of life, our customers are encouraged to dispose of them in accordance with the product disposal and/or recovery programs prescribed by their nation or company.

Trademarks

Product names mentioned herein are used for identification purposes only and may be trademarks and/or registered trademarks of their respective companies.

Using this Manual

Audience and Scope

The cPCI-3920 User's Manual is intended for hardware technicians and systems operators with knowledge of installing, configuring and operating industrial grade CompactPCI modules.

Manual Organization

This manual is organized as follows:

Chapter 1, Overview: Introduces the cPCI-3920 and package contents.

Chapter 2, Specifications: Presents detailed specification information, power consumption, and mechanical layout.

Chapter 3, Functional Description: Describes the cPCI-3920 main functions and board interfaces.

Chapter 4, Getting Started: Describes the installation instructions of the cPCI-3920.

Chapter 5, Driver Installation: Describes the driver installation procedures.

Chapter 6, Watchdog Timer: Describes the Watchdog Timer functionality.

Chapter 7, BIOS Setup Utility: Describes the AMIBIOS®8 BIOS setup utility.

Important Safety Instructions: Presents safety instructions all users must follow for the proper setup, installation and usage of equipment and/or software.

Getting Service: Contact information for ADLINK's worldwide offices.

Conventions

Take note of the following conventions used throughout this manual to make sure that users perform certain tasks and instructions properly.



NOTE:

Additional information, aids, and tips that help users perform tasks.



Information to prevent **minor** physical injury, component damage, data loss, and/or program corruption when trying to complete a task.



Information to prevent **serious** physical injury, component damage, data loss, and/or program corruption when trying to complete a specific task.

This page intentionally left blank.

Table of Contents

Revision History	ii
Preface	iii
List of Tables	ix
List of Figures	xi
1 Overview	1
1.1 Introduction	1
1.2 Features.....	2
1.3 Block Diagram	3
1.4 Product List.....	4
1.5 Package Contents	5
2 Specifications	7
2.1 CPU, memory, and chipset.....	7
2.2 Interfaces	7
2.3 Software	9
2.4 Mechanical.....	9
2.5 Environmental.....	9
2.6 I/O Connectivity Table	10
2.7 Power Requirements	11
2.8 Mechanical Dimensions	15
2.9 Board Layout	17
3 Functional Description	23
3.1 CPU, Memory and Chipset	23
3.2 Peripherals.....	30
3.3 Board Interfaces	34
3.4 Board Interfaces on RTM.....	51
4 Getting Started	57
4.1 Safety Requirements	57
4.2 Installing the USB Flash Disk	58
4.3 Installing the Hard Disk Drive (cPCI-3290B only)	59
4.4 Installing the cPCI-3920 to the Chassis.....	60
4.5 RTM (cPCI-R3920) Installation.....	61
4.6 Hot Swap Procedures.....	61

5	Driver Installation.....	63
6	Watchdog Timer.....	65
6.1	WDT Overview.....	65
6.2	Using the Watchdog Timer in an Application.....	66
7	BIOS Setup Utility	71
7.1	Starting the BIOS	71
7.2	Main Setup.....	75
7.3	Advanced BIOS Setup	77
7.4	PCI/PnP Setup.....	89
7.5	Boot Setup	90
7.6	Security Setup.....	94
7.7	Chipset Setup	97
7.8	Exit Menu	99
	Important Safety Instructions.....	101
	Getting Service	103

List of Tables

Table 2-1:	I/O Connectivity	10
Table 2-2:	CompactPCI input voltage characteristics	11
Table 2-3:	Power consumption of Core™ 2 Duo LV (L7400) ..	12
Table 2-4:	Power consumption of Core™ 2 Duo LV (U2500) ..	13
Table 2-5:	Power consumption of Celeron M LV(423)	14
Table 3-1:	Supported Processors, Power Dissipation	25
Table 3-2:	SMBus Devices and Addresses	32
Table 3-3:	LED Function Descriptions	33
Table 3-4:	Front Panel USB Connector Pin Definition	34
Table 3-5:	Onboard USB Connector Pin Definition	35
Table 3-6:	VGA Connector CN3 Pin Definition	38
Table 3-7:	Gigabit Connector CN7/CN8 Pin Definitions	39
Table 3-8:	Ethernet LED Status Definitions	40
Table 3-9:	Board-to-Board Connector Pin Definition	41
Table 3-10:	PS/2 Keyboard/Mouse Connector Pin Definition	42
Table 3-11:	COM3 Serial Port Connector Pin Definition	43
Table 3-12:	COM4 Serial Port Connector Pin Definition	43
Table 3-13:	COM4 Mode Switch Settings	44
Table 3-14:	SATA0 Connector Pin Definition	46
Table 3-15:	CompactPCI J1 Pin Assignment	48
Table 3-16:	CompactPCI J2 Pin Assignment	50
Table 3-17:	RTM USB Connector Pin Definitions	51
Table 3-18:	RTM Gigabit Connector Pin Definitions	52
Table 3-19:	COM1 Serial Port Connector Pin Definition	53
Table 3-20:	COM2 Serial Port Connector Pin Definition	53
Table 3-21:	SATA1-3 Connectors Pin Definition	54
Table 3-22:	CompactPCI rJ2 Pin Assignment	56

This page intentionally left blank.

List of Figures

Figure 1-1: cPCI-3920 Block Diagram	3
Figure 2-1: cPCI-3920 Mechanical Dimensions.....	15
Figure 2-2: cPCI-R3920 Mechanical Dimensions	16
Figure 2-3: cPCI-3920 Board Layout	17
Figure 2-4: cPCI-3920A Assembly and Front Panel	18
Figure 2-5: DB-3920L2 Daughter Board Layout	19
Figure 2-6: cPCI-3920B Assembly and Front Panel	20
Figure 2-7: cPCI-R3920(T) Board Layout and Front Panel	21
Figure 3-1: Intel® 3100 Chipset Block Diagram.....	26
Figure 3-2: USB Flash Disk Mechanical Layout	36
Figure 6-1: cPCI-3920 Watchdog Timer Architecture	65

This page intentionally left blank.

1 Overview

1.1 Introduction

The cPCI-3920 is a highly integrated 3U CompactPCI SBC in single slot (4HP) or dual slot (8HP) width form factor. It has been designed to support Intel® lower power Core™ 2 Duo, Core™ Duo and Celeron® M processors in FC-BGA package with a range of 1.0GHz to 1.5GHz at FSB 533MHz to 667MHz. They deliver optimized power-efficient computing and outstanding dual core performance with lower power consumption.

The cPCI-3920 is based on the server-class Intel® 3100 chipset (Whitmore Lake) which combines Memory Controller Hub and I/O Controller Hubs into a single component, significantly conserving board real estate and power consumption. The Intel® 3100 chipset is the first Integrated Intel® chipset optimized for embedded, communications, and storage applications.

The cPCI-3920 supports registered ECC type, single channel DDR2 400MHz soldered onboard memory with a maximum capacity of up to 2GB. The board supports one 32-bit/33MHz CompactPCI interface acting as system master CPU only.

The cPCI-3920 offers versatile I/O ports like two Gigabit Ethernet ports, two COM ports, up to three USB 2.0 ports, PS/2 Keyboard/Mouse, and VGA port on the front panel. A Rear Transition Module (RTM) is also available and provides an additional two USB 2.0 ports, two COM ports, and two Gigabit Ethernet ports switched from the front panel.

Storage features of the cPCI-3920 include a pin header and mounting space for an onboard USB NAND flash module, and one Serial ATA interface with mounting space for a 2.5" HDD in the 8HP version. There are also three 7-pin Serial ATA interfaces available on the RTM for additional storage expansion.

Designed for stability and packaged in a rugged format, the cPCI-3920 is suitable for long life applications situated in industrial environments, including I/O intensive applications where only one slot is available for the CPU. Components which have high temperature tolerance have been selected from embedded technology programs, and therefore offer long-term availability.

1.2 Features

- ▶ 3U CompactPCI SBC in 4HP or 8HP width form factor
- ▶ Low power Intel Core 2 Duo 1.5GHz, Core™ Duo 1.2GHz, Celeron® M 1.0GHz processors
- ▶ Intel® 3100 chipset (Memory and I/O Hub integrated chip)
- ▶ Single channel DDR2 registered and ECC memory at 400MHz
- ▶ Two PCI-Express Gigabit Ethernet ports in the front or RTM
- ▶ Support USB 2.0 NAND flash module, up to 8GB
- ▶ Supports one 2.5" Serial ATA hard drive onboard and three Serial ATA interfaces on RTM
- ▶ Up to five USB ports and four serial ports

1.3 Block Diagram




Figure 1-1: cPCI-3920 Block Diagram

1.4 Product List

Products included in the cPCI-3920 Series include:

SBC

- ▶ cPCI-3920A: single-slot (4HP) width 3U CompactPCI featuring Intel LV Core 2 Duo 1.5GHz, Core Duo 1.2GHz or ULV Celeron 1.0GHz processors; 512MB, 1GB or 2GB onboard memory; optional USB flash disk module
- ▶ cPCI-3920B: dual-slot(8HP) width 3U CompactPCI featuring Intel LV Core 2 Duo 1.5GHz, Core Duo 1.2GHz or ULV Celeron 1.0GHz processors; 512MB, 1GB or 2GB onboard memory; optional USB flash disk module and 2.5" SATA hard drive

Rear Transition Module

- ▶ cPCI-R3920: Rear Transition Module for cPCI-3920 SBCs with 50mm width
- ▶ cPCI-R3920T: Rear Transition Module for cPCI-3920 SBCs with 80mm width

Accessories

- ▶ USB flash disk module, optional 2GB, 4GB or 8GB
- ▶ 2.5" Serial ATA hard drive

Contact your ADLINK representative to purchase accessories.

1.5 Package Contents

The cPCI-3920 is packaged with the following components. If any of the items on the contents list are missing or damaged, retain the shipping carton and packing material and contact the dealer for inspection. Please obtain authorization before returning any product to ADLINK. The packing contents of the cPCI-3920 Series are non-standard configurations and may vary depending on customer requests.

CPU module

- ▶ The cPCI-3920 Series CPU Module
 - ▷ CPU, RAM, and HDD specifications will differ depending on options selected
 - ▷ Thermal module is assembled on the board
 - ▷ Battery daughter board is assembled on the board
 - ▷ HDD bracket is assembled on the 8HP version
- ▶ Four screws for hard drive
- ▶ Y-cable for PS/2 combo port (8HP version only)
- ▶ ADLINK All-in-One CD
- ▶ User's manual

Rear Transition Module

- ▶ cPCI-R3920 or cPCI-R3920T



NOTE:

The contents of non-standard cPCI-3920 configurations may vary depending on the customer's requirements.

CAUTION: This product must be protected from static discharge and physical shock. Never remove any of the components except at a static-free workstation. Use the anti-static bag shipped with the product when putting the board on a surface. Wear an anti-static wrist strap properly grounded on one of the system's ESD ground jacks when installing or servicing system components.

This page intentionally left blank.

2 Specifications

2.1 CPU, memory, and chipset

Processor	uFC-BGA Intel® Core™ 2 Duo LV (L7400) 1.5 GHz, FSB 667MHz, 4 MB L2 cache
	uFC-BGA Intel Intel® Core™ Duo ULV (U2500) 1.2 GHz, FSB 533MHz, 2 MB L2 cache
	uFC-BGA Intel Intel® Celeron® M ULV (423) 1.06 GHz, FSB 533MHz, 1 MB L2 cache
Chipset	Intel® 3100 chipset
Memory	Single channel soldered onboard registered ECC DDR2 SDRAM at 400MHz up to 2GB

2.2 Interfaces

CompactPCI Standard	PICMG® 2.0 R3.0 PICMG® 2.1 R2.0
CompactPCI Bus	32-bit/33MHz PCI bus
Display	XGI Volari Z11 PCI-Express x1 Graphics Controller 32MB DDR2-400 SDRAM memory Up to 1600x1200@70Hz 24bit color
Ethernet	PCI-Express x4 Intel® 82571EB dual port Ethernet controller Two GbE egress ports on the front panel or on the rear panel by BIOS selection
USB	4x USB channels from 3100 chipset
	Channel 0 is for 9 pin header, space reserved for horizontal USB flash disk module
	Channel 1 is connected to the front panel
	Channel 2 is connected to the front panel (8HP only)
	Channel 3 is connected to 4-port hub controller with one channel routed to the 8HP front panel and two channels routed to the RTM

Serial Port	4x serial ports
	Two DB-9 ports on the front panel, one RS-232 and one RS-232/422/485/485+ (8HP only)
	Two ports are routed to RTM with one DB-9 port on rear panel and one pin header onboard
Serial ATA	4x Serial ATA channels:
	One SATA connector onboard, 2.5" HDD space reserved (8HP only)
	Three channels are routed to RTM with pin headers onboard
Front panel I/O	cPCI-3920 main board
	1x USB 2.0 port
	1x VGA port
	2x GbE port
	1x system reset button
	Power, WDT, CPU over-temperature LED
	DB-3920L2 daughter board (8HP only)
	1x RS-232 port
	1x RS-232/422/485/485+ selectable port
	1x PS/2 combo port for keyboard and mouse
	2x USB 2.0 port
Board I/O Interfaces	cPCI-3920 main board
	1x pin header for USB flash disk module
	DB-3920L2 daughter board (8HP only)
	1x SATA port (signal and power for onboard HDD)
	cPCI-R3920 rear transition module
	3x SATA ports (7-pin)
	10-pin RS232 port
Rear panel I/O	2x USB 2.0 port
	2x GbE port (share the same channels with front panel GbE ports, selected by BIOS setting)
	1x RS-232 port

2.3 Software

BIOS	AMI 16Mbit FWH
Supported OS	Microsoft® Windows® XP Professional
	Microsoft® Windows® Server 2003
	Microsoft® Windows® Vista Enterprise, 32-bit version
	RedHat Fedora Core 8
	Contact ADLINK for other OS availability

2.4 Mechanical

Form factor	cPCI-3920: 3U 4HP/8HP CompactPCI
	cPCI-R3920(T): 3U 4HP CompactPCI
Dimensions	cPCI-3920: 100mmx 160mm (LxW)
	cPCI-R3920: 100mm x 50mm (LxW)
	cPCI-R3920T: 100mmx 80mm (LxW)

2.5 Environmental

Operating temperature	Standard: 0 to 60°C
	Extended temperature: -20 to 70°C
Storage temperature	-40°C to 85°C
Humidity	5% to 95% non-condensing
Shock	15G peak-to-peak, 11ms duration, non-operation
Vibration	Non-operating: 1.88G rms, 5 to 500 Hz, each axis
	Operating: 1.88G rms. 5 to 500Hz, each axis, with USB flash disk (without HDD)
Compliance	CE, FCC Class A

2.6 I/O Connectivity Table

	cPCI-3920A		cPCI-3920B		cPCI-R3920(T)	
	Faceplate	Board	Faceplate	Board	Faceplate	
GbE	Y x2	--	Y x2	--	Yx2	--
USB	Y	Y (9-pin)	Y x3	Y (9-pin)	Yx2	--
VGA	Y	--	Y	--	--	--
COM	--	--	Y (DB-9) x2	--	Y (DB-9)	Y (10-pin)
SATA	--	--	--	Y	--	Y x3 (7-pin)
PS/2 KB/MS	--	--	Y	--	--	--
LED	Y x3	--	Y x3	--	--	--
Reset Button	Y	--	Y	--	--	--

Table 2-1: I/O Connectivity

2.7 Power Requirements

In order to guarantee a stable functionality of the system, it is recommended to provide more power than the system requires. An industrial power supply unit should be able to provide at least twice as much power as the entire system requires. An ATX power supply unit should be able to provide at least three times as much power as the entire system requires.

The tolerance of the voltage lines described in the CompactPCI specification (PICMG 2.0 R3.0) is +5%/-3% for 5, 3.3 V and $\pm 5\%$ for $\pm 12\text{V}$. This specification is for power delivered to each slot and it includes both the power supply and the backplane tolerance.

Voltage	Nominal Value	Tolerance	Max. Ripple (P - P)
5V	+5.0 VDC	+5% / -3%	50 mV
3.3V	+3.3 VDC	+5% / -3%	50 mV
+12V	+12 VDC	+5% / -5%	240 mV
-12V	-12 VDC	+5% / -5%	240 mV
V I/O (PCI I/O Buffer Voltage)	+3.3 VDC or +5 VDC	+5% / -3%	50 mV
GND			

Table 2-2: CompactPCI input voltage characteristics

Power Consumption

The following tables provide information on the power consumption of cPCI-3920.

**Processor: Intel® Core™ 2 Duo LV (L7400) 1.5GHz,
FSB 667MHz, 4MB L2 cache**

Function	Configuration		
Memory	DDR2 400 1GB		
SATA Hard Drive	External 3.5"HDD		
Backplane	ADLINK cBP-3208R Rev.B2		
Power Supply	ZIPPY HG2-6350P 350W		
DOS			
Power requirement	+3.3V	+5V	Total
Current (A)	1.53	4.41	
Watts (W)	5.05	22.05	27.10
Linux, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.63	3.53	
Watts (W)	5.38	17.65	23.03
Windows® XP, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.62	4.63	
Watts (W)	5.35	23.15	28.50
Windows® XP, CPU 100% Usage			
Power requirement	+3.3V	+5V	Total
Current (A)	1.61	6.02	
Watts (W)	5.31	30.10	35.41

Table 2-3: Power consumption of Core™ 2 Duo LV (L7400)

**Processor: Intel® Core™ Duo (U2500) 1.2GHz, FSB 533MHz,
2MB L2 cache**

Function	Configuration		
Memory	DDR2 400 1GB		
SATA Hard Drive	External 3.5"HDD		
Backplane	ADLINK cBP-3208R Rev.B2		
Power Supply	ZIPPY HG2-6350P 350W		
DOS			
Power requirement	+3.3V	+5V	Total
Current (A)	1.54	3.50	
Watts (W)	5.08	17.50	22.58
Linux, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.64	3.30	
Watts (W)	5.41	16.50	21.91
Windows® XP, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.68	3.71	
Watts (W)	5.38	18.55	23.93
Windows® XP, CPU 100% Usage			
Power requirement	+3.3V	+5V	Total
Current (A)	1.63	4.30	
Watts (W)	5.38	21.50	26.88

Table 2-4: Power consumption of Core™ 2 Duo LV (U2500)


**Processor: Intel® Celeron M LV(423) 1.07GHz, FSB 533MHz,
1MB L2 cache**

Function	Configuration		
Memory	DDR2 400 1GB		
SATA Hard Drive	External 3.5"HDD		
Backplane	ADLINK cBP-3208R Rev.B2		
Power Supply	ZIPPY HG2-6350P 350W		
DOS			
Power requirement	+3.3V	+5V	Total
Current (A)	1.51	3.27	
Watts (W)	4.98	16.35	21.33
Linux, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.60	3.12	
Watts (W)	5.28	15.60	20.88
Windows® XP, Idle			
Power requirement	+3.3V	+5V	Total
Current (A)	1.59	3.36	
Watts (W)	5.25	16.80	22.05
Windows® XP, CPU 100% Usage			
Power requirement	+3.3V	+5V	Total
Current (A)	1.59	3.64	
Watts (W)	5.25	18.20	23.45

Table 2-5: Power consumption of Celeron M LV(423)

2.8 Mechanical Dimensions

cPCI-3920A



cPCI-3920B





Figure 2-1: cPCI-3920 Mechanical Dimensions

cPCI-R3920



cPCI-R3920T





Figure 2-2: cPCI-R3920 Mechanical Dimensions

2.9 Board Layout


cPCI-3920 Board Layout



U6	Processor	CN2	USB port
U7	Chipset	CN3	VGA port
U5	Transformer	CN7	Ethernet port
U15	Graphics controller	CN8	Ethernet port
U19	Ethernet controller	CN4	DB-3920L2 daughter board connector
U25	SDRAM	CN5	USB pin header
J1	CompactPCI J1 connector	J2	CompactPCI J2 connector

Figure 2-3: cPCI-3920 Board Layout

cPCI-3920A Assembly Outline



cPCI-3920A Front Panel




Figure 2-4: cPCI-3920A Assembly and Front Panel

Reset Button

- ▶ RST

Temperature LED

- ▶ Hot (red): CPU Overtemperature Status, connected to the CPU signal PROCHOT

Status LEDs


- ▶ WDT (yellow): Watchdog Status
- ▶ PWR (green): Power Supply Status

Gigabit Ethernet LEDs

- ▶ SPEED ON (green): 1000Mbps
- ▶ SPEED OFF: 10Mbps or 100Mbps
- ▶ ACT (yellow): Ethernet Link Activity

DB-3920L2 Daughter Board Components Layout


The DB-3920L2 Daughter Board extends the cPCI-3920 from 4HP (cPCI-3920A) to 8HP (cPCI-3920B) version. This additional capability opens up the broadest range of expansion possibilities. The DB-3920L2 module has been designed to include two COM ports, a PS/2 keyboard and mouse port, two USB 2.0 interfaces and a 2.5" SATA hard disk interface.



CN1-2	Serial port	CN5-2	USB port
CN2-2	PS/2 Keyboard/ Mouse	CN6-2	Serial port
CN3-2	Serial ATA connector	SW	COM4 mode switches
CN4-2	USB port		

Figure 2-5: DB-3920L2 Daughter Board Layout

cPCI-3920B Assembly Outline



cPCI-3920B Front Panel





Figure 2-6: cPCI-3920B Assembly and Front Panel

cPCI-R3920(T) Board Layout

The cPCI-3920 Series offer two version rear transition modules with the same functionality but different dimensions. The cPCI-R3920 is designed with a 50mm width and the cPCI-R3920T is designed with a 80mm width



CN1-R	10 pin RS-232 port	CN5-R	SATA port
CN2-R	SATA port	CN6-R	Dual Ethernet ports
CN3-R	RS232 port	CN7-R	USB port
CN4-R	SATA port	CN8-R	USB port

cPCI-R3920(T) Front Panel




Figure 2-7: cPCI-R3920(T) Board Layout and Front Panel

This page intentionally left blank.

3 Functional Description

The following sections describe the cPCI-3920 main functions and board interfaces.

3.1 CPU, Memory and Chipset

CPU: Intel® Core™ Duo and Intel® Core™2 Duo

The cPCI-3920 supports the latest Intel® Core™ Duo and Intel® Core™2 Duo processor family up to speeds of 1.5 GHz with up to 667 MHz FSB. The Intel® Core™ Duo consists of two cores and up to 2 MB L2 cache shared by both cores. The Intel® Core™2 Duo consists of two cores, up to 4 MB L2 cache shared by both cores, Intel Extended Memory 64 Technology (Intel EM64T), and enhanced address range for up to 64 GB memory. The Intel® Core™ Duo and the Intel® Core™2 Duo processors deliver optimized power-efficient computing and outstanding dual-core performance with low power consumption.

The Intel® Core™ Duo and the Intel® Core™2 Duo support the latest Intel's Virtualization Technology (VT), which allows a platform to run multiple operating systems and applications in independent partitions, such as performing system upgrades and maintenance without interrupting the system or the application, keeping software loads and virus attacks separate, combining multiple servers in one system, etc. With processor and I/O enhancements to Intel's various platforms, Intel Virtualization Technology improves the performance and robustness of today's software-only virtual machine solutions.

Furthermore, the Intel® Core™ Duo and the Intel® Core™2 Duo also support the Intel SpeedStep technology which enables real-time dynamic switching of the voltage and frequency between several modes. This is achieved by switching the bus ratios, core operating voltage, and core processor speeds without resetting the system.

The following list sets out some of the key features of the Intel® Core™ Duo and the Intel® Core™2 Duo processors:

- ▶ Two mobile execution cores in one single processor
- ▶ Support of Intel's Virtualization Technology (Vanderpool)
- ▶ Support of Intel Architecture with Dynamic Execution
- ▶ Outstanding dual-core performance with low power consumption
- ▶ On die, primary 32 KB instruction cache and 32KB write-back data cache
- ▶ On die, L1 and L2 cache with Advanced Transfer Cache Architecture
 - ▷ Intel® Core™ Duo processor (ULV), 1.2 GHz, 533 MHz FSB, 2 MB L2 cache
 - ▷ Intel® Core™2 Duo processor (LV), 1.5 GHz, 667 MHz FSB, 4 MB L2 cache
- ▶ Advanced Branch Prediction and Data Prefetch Logic
- ▶ Streaming SIMD Extensions 3 (SSE3)
- ▶ Up to 667 MHz, Source-Synchronous Front Side Bus (FSB)
- ▶ Advanced Power Management features including Enhanced Intel SpeedStep technology
- ▶ Intel Extended Memory 64 Technology for 64-bit computing (only with the Intel® Core™2 Duo)
- ▶ Enhanced address range for up to 64 GB memory (only with the Intel® Core™ Duo)

Intel® Celeron® M

The cPCI-3920 supports the low power 1.07 GHz Intel® Celeron® M processor with 533 MHz FSB. The Intel® Celeron® M consists of one core and 1 MB L2 cache.

The following list sets out some of the key features of the Intel® Celeron® M processor:

- ▶ Supports Intel architecture with dynamic execution
- ▶ High-performance, low-power core featuring architectural innovations like micro-ops fusion and advanced stack man-

agement that reduce the number of micro-ops handled by the processor.

- ▶ On-die, primary 32-kB instruction cache and 32-kB, write-back, data cache
- ▶ On-die, 1 MB second level cache with Advanced Transfer Cache architecture
- ▶ Advanced branch prediction and data prefetch logic
- ▶ Streaming SIMD extensions 2 (SSE2) that enables break-through levels of performance in multimedia applications including 3D graphics, video decoding/encoding, and speech recognition.
- ▶ 533-MHz, source-synchronous front side bus (FSB)
- ▶ Advanced power management features
- ▶ Maintained support for MMX_ technology (technology designed to accelerate multimedia and communications software)
- ▶ Compatible with IA-32 software

Supported Processors, Maximum Power Dissipation

The following tables indicate the processors supported on the cPCI-3920 and their maximum power dissipation.

Speed	Intel® Celeron® M 1.07 GHz (ULV ⁽²⁾)	Intel® Core Duo 1.2GHz (ULV ⁽²⁾)	Intel® Core 2 Duo 1.5GHz (LV ⁽¹⁾)
Package	µFCBGA	µFCBGA	µFCBGA
L2 Cache	1MB	2MB	4MB
FSB	533 MHz	533 MHz	667 MHz

(1) LV: Low Voltage

(2) ULV: Ultra low Voltage

Frequency Mode	Intel® Celeron® M 1.07 GHz (ULV) 1MB L2 Cache	Intel® Core Duo 1.2GHz (ULV) 2MB L2 Cache	Intel® Core 2 Duo 1.5GHz (LV) 4MB L2 Cache
Maximum Power HFM ⁽³⁾	5.5W	9W	17W

(3) HFM: High Frequency Mode (maximum frequency of the CPU)

Table 3-1: Supported Processors, Power Dissipation

Memory

The cPCI-3920 supports a single soldered channel DDR2 memory with Error Checking and Correcting (ECC) running at 400 MHz. The available memory module configuration is 1 GB. 2 GB available on request, please contact your ADLINK representative.



NOTE:

Memory configuration changes can only be performed at the factory. Failure to comply with the above may result in damage to your board or improper operation.

Intel® 3100 Chipset Overview

The Intel® 3100 Chipset is a single integrated chip that contains the functionality of a Memory Controller Hub and an I/O Controller Hub. In this document the Memory Controller Hub unit and I/O Controller Hub unit in the Intel® 3100 Chipset are referenced as IMCH (Integrated Memory Controller Hub) and IICH (Integrated I/O Controller Hub) respectively.




Figure 3-1: Intel® 3100 Chipset Block Diagram

PCI Express

The Intel 3100 Chipset provides one configurable x8 PCI Express interface with a maximum theoretical bandwidth of 4 GByte/s. The x8 PCI Express interface may alternatively be configured as two independent x4 PCI Express interfaces with a maximum theoretical bandwidth of 2 GBytes/s each. The Intel® 3100 Chipset also supports an additional x4 PCI Express interface with a maximum theoretical bandwidth of 2 GBytes/s which may alternatively be configured as four independent x1 PCI Express interfaces.

IICH

I/O Controller Hub (IICH) functions are integrated into the Intel® 3100 Chipset, eliminating the requirement for a legacy I/O bridge.

I/O Controller Hub Feature set comprises:

- ▶ PCI Express Interface
- ▶ Low Pin Count (LPC) Interface
- ▶ Firmware Hub (FWH) Interface
- ▶ Integrated Serial ATA (SATA) Host Controllers:
 - ▷ Independent DMA operation on six ports
 - Four ports in SATA 1.0a and AHCI mode
 - Six ports in AHCI mode only
 - ▷ Data transfer rates up to 150 Mbyte/s
- ▶ Two controllers with up to four USB 2.0 ports:
 - ▷ One EHCI USB 2.0 Host Controller to support a total of four ports (shared with the UHCI ports)
 - ▷ Two UHCI Host Controllers to support a total of four ports (shared with the EHCI ports)
- ▶ Interrupt Controller
- ▶ Power Management Logic
- ▶ DMA Controller
- ▶ Timers Based on 82C54
- ▶ High Precision Event Timers (HPET)
- ▶ Real Time Clock with 256-byte Battery-backed CMOS RAM

- ▶ System TCO Reduction Circuits
- ▶ SMBus
- ▶ Watchdog Timers
- ▶ PCI 2.3 Interface
- ▶ Two fully functional serial ports
- ▶ 38 General Purpose I/Os (GPIO)

IMCH

The Intel® 3100 Chipset provides an integrated memory controller for direct-connection to one channel of DDR2-400 (unstacked) registered memory devices with ECC. Peak theoretical memory data bandwidth using DDR2-400 is 3.2 GByte/s

Volari™ Z11 Graphics Controller

Volari™ Z11 GPU is the extreme programmable GPU of the XGI 2D GPU family. The Volari™ Z11 integrates a PCI-Express 1x controller and a 64-bit 2D graphics engine. It offers a flexible 16-bit DDR-II memory interface. The Z11 also incorporates a configurable 3.3V DVO digital interface to support a third party LVDS/TMDS transmitter. It can achieve high 2D performance with a memory interface supporting a bandwidth of up to 1 GB/s (DDR-II @250MHz).

Volari™ Z11 GPU main features:

- ▶ PCI-Express 1x Bus Interface
 - ▷ Supports PCI-E local bus standard Revision 1.1 compliant
- ▶ High Performance 2D Accelerator
 - ▷ Built-in hardware command queue
 - ▷ Built-in Direct Draw Accelerator
 - ▷ Built-in GDI 2000 Accelerator
 - ▷ Built-in an 1T pipelined 64-bit BITBLT graphics engine
 - ▷ Supports memory-mapped, zero wait-state, burst engine write
 - ▷ Built-in 64x64x2 bit-mapped mono hardware cursor
- ▶ High Efficient BroadBahn™ Memory Architecture

- ▷ Supports DDR-II SDRAM memory
- ▷ 32 MB memory configuration
- ▷ Supports VGA BIOS auto memory size detection
- ▶ High Performance Flat Panel Display Interface
 - ▷ Supports graphics mode up to 1600x1200@70Hz 16M colors
- ▶ High Integration
 - ▷ Built-in CRT FIFO to support ultra high resolution graphics modes and reduce CPU wait-state
 - ▷ Built-in programmable 24-bit true-color RAMDAC with 230 MHz pixel clock
- ▶ Resolution, Color & Frame Rate
 - ▷ Supports 230 MHz pixel clock
 - ▷ Supports VESA standard super high resolution graphics modes
 - 4:3 resolution up to 1600x1200 256/32K/64K/16M colors 70Hz
 - Wide Screen resolution modes
 - Low resolution modes
 - ▷ Supports virtual screen up to 4096x4096
- ▶ Power Management
 - ▷ Supports power management for VGA monitor
- ▶ Multimedia Application
 - ▷ Supports DDC1, DDC2B and DDC 3.0 specifications
 - ▷ Supports RAMDAC snoop fir multimedai applications
- ▶ Miscellaneous
 - ▷ Lead-free package
 - ▷ RoHS compliance



NOTE:

The Z11 doesn't support the Linux X11 performance bench test, which changes display mode frequently during every screen page. The display flickers when performing the X11 performance bench test under Linux.

3.2 Peripherals

The following standard peripherals are available on the cPCI-3920 board:

Timer

The cPCI-3920 is equipped with the following timers:

Real-Time Clock

The IICH contains real-time clock with 256-byte of battery-backed RAM.

The real-time clock performs timekeeping functions and includes 256 bytes of general purpose battery-backed CMOS RAM. Features include an alarm function, programmable periodic interrupt and a 100-year calendar. All battery-backed CMOS RAM data remains stored in an additional EEPROM. This prevents data loss in case the cPCI-3920 is operated without battery.

Counter/Timer

Three 8254-style counter/timers are included on the cPCI-3920 as defined for the PC/AT (System Timer, Refresh Request, Speaker Tone Output).

In addition to the three 8254-style counters, the IICH includes three High Precision Event Timers (HPET) that may be used by the operating system. They are implemented as a single counter each with its own comparator and value register. They support One-shot and periodic interrupts.

Watchdog Timer

The cPCI-3920 provides a Watchdog Timer that is programmable for a timeout period ranging from 1 ms to 1050 sec. Failure to trigger the Watchdog Timer in time results in a system reset, an interrupt, or NMI. In the dual-stage mode, a combination of both NMI, and reset if the Watchdog is not serviced. A hardware status flag will be provided to determine if the Watchdog Timer generated the reset.

Battery

The cPCI-3920 is provided with a 3.0 V “coin cell” lithium battery for the RTC. To replace the battery, proceed as follows:

- ▶ Turn off power
- ▶ Remove the battery
- ▶ Place the new battery in the socket.
- ▶ Make sure that you insert the battery the right way round.
The plus pole must be on the top!

The lithium battery must be replaced with an identical battery or a battery type recommended by the manufacturer. Suitable batteries include the Varta CR2025 and Panasonic BR2020.



NOTE:

The user must be aware that the battery's operational temperature range is less than that of the cPCI-3920's storage temperature range. For exact range information, refer to the battery manufacturer's specifications.



NOTE:

Care must be taken to ensure that the battery is correctly replaced. The battery should be replaced only with an identical or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instructions. The typical life expectancy of a 225 mAh battery (Varta CR2032) is 4-5 years with an average on-time of 8 hours per working day at an operating temperature of 30°C. However, this typical value varies considerably because the life expectancy is dependent on the operating temperature and the standby time (shutdown time) of the system in which it operates. To ensure that the lifetime of the battery has not been exceeded, it is recommended to exchange the battery after 3-4 years.

Reset

A reset will be generated by the following conditions:

- ▶ Pressing the front panel reset button
- ▶ Watchdog overflow
- ▶ CompactPCI backplane PRST# input (CompactPCI connector J2, pin C17)

SMBus Devices

The cPCI-3920 provides a System Management Bus (SMBus) for access to several system monitoring and configuration functions. The SMBus consists of a two-wire I2C bus interface.

The following table describes the function and address of every onboard SMBus device.

Device	SMBus Address
Clock Buffer	DCh
Clock Generator	D2h
SPD	A0h
EEPROM (Board VPD)	AEh

Table 3-2: SMBus Devices and Addresses

Thermal Management / System Monitoring

The W83792AG can be used to monitor several critical hardware parameters of the system, including power supply voltages and temperatures, all of which are very important for the proper operation and stability of a high-end computer system.

The voltages +12 V, +5 V, +3.3 V, and Vcore are supervised. The temperature sensors monitor the CPU temperature and the ambient temperature to ensure that the system is operating at a safe temperature level. If the CPU temperature is too high, the sensor automatically reduces the CPU clock frequency, depending on the mode chosen in the BIOS settings.

FWH Flash Memory

For simple BIOS updating a standard onboard 16 Mbit Firmware Hub device is used. The FWH stores both the system BIOS and graphics BIOS. It can be updated as new versions of the BIOS become available.

LED Functions

There are three LEDs on the front panel, below table shows the function of LEDs.

Name	Color	Status	Function description
HOT	Red	BLINK	CPU reaches or exceeds max. operating temperature
		OFF	CPU below max. operating temperature
WDT	Yellow	ON	WDT function enable
		OFF	WDT function disable
PWR	Green	ON	Power on
		OFF	Power off

Table 3-3: LED Function Descriptions

3.3 Board Interfaces

USB Interfaces

The cPCI-3920 supports six USB 2.0 ports:

- ▶ one front I/O
- ▶ two front I/O on DB-3920L2 module
- ▶ one onboard to connect a Flash disk
- ▶ two on the Rear I/O module.

On the USB 2.0 front panel port, USB cable with up to 5 meters in length can be used.

On the USB 2.0 Rear I/O ports, it is strongly recommended to use a cable below 3 meters in length for USB 2.0 devices.

The USB 2.0 ports are high-speed, full-speed, and low-speed capable. Hi-speed USB 2.0 allows data transfers of up to 480 Mb/s - 40 times faster than a full-speed USB (USB 1.1). One USB peripheral may be connected to each port.

To connect more USB devices than there are available ports, an external hub is required.

Front Panel USB Connectors (CN2, CN4 -2, CN5-2)

Pin #	Signal Name
1	Vcc
2	UV0-
3	UV0+
4	GND




Table 3-4: Front Panel USB Connector Pin Definition



NOTE:

The cPCI-3920 host interfaces can be used with maximum 500 mA continuous load current as specified in the Universal Serial Bus Specification, Revision 2.0. Short-circuit protection is provided. All the signal lines are EMI-filtered.

Onboard USB Pin Header (CN5)

The onboard USB device (CN5 pin header, 2.54mm pitch) is used to connect a USB Flash Disk.

The following figure and table provide pinout information for the onboard USB pin header CN5:

Pin	Signal	Function	I/O
1	Vcc	VCC	--
2	Uv0-	Differential USB-	I/O
3	Uv0+	Differential USB+	I/O
4	GND	GND	--
5	--	Not connected	--
6	--	Not used	--
7	GND	GND	--
8	--	Not used	--
9	--	Not used	--
10	--	Not used	--




Table 3-5: Onboard USB Connector Pin Definition

USB Flash Disk Mechanical Layout

- ▶ Maximum space reserved for USB flash disk is 50mm x 30mm (LxW)
- ▶ The distance between the centers of connector and screw hole is 27.3mm~27.9mm
- ▶ Maximum allowable connector height is 9.78mm (under 4HP)




Figure 3-2: USB Flash Disk Mechanical Layout

Graphics Controller

The Volari™ Z11 graphics controller incorporates a powerful 64-bit graphics engine to enhance the performance of 2D operations. The capabilities of the graphics engine include, but are not limited to BitBlt, Color Expansion, Enhanced Color Expansion, Line Drawing, Transparent BitBlt, and Rectangle Fill.

For all enhanced 256 color (8 bpp), 32k & 64k hi-color (16 bpp), and 16M true color (32 bpp) graphics modes, the 2D engine supports the following functions:

- ▶ 256 raster operations
- ▶ Rectangle fill
- ▶ Color expansion
- ▶ Enhanced Color expansion
- ▶ Line drawing with styled pattern
- ▶ Built-in bytes pattern registers
- ▶ Built-in 8x8 mask registers
- ▶ Rectangle Clipping Transparent BitBlt with source and destination keys
- ▶ Source data in command queue Bitblt

The engine also supports new GDI 2000 functions

PCI Bus Interface

The Volari™ Z11 GPU is a native PCI-E device which connects directly to the PCI-E bus onboard the motherboard. The Z11 decodes 32-bit addresses and configures the device based on the applicable control lines between the target and initiator. The GPU can execute both I/O and memory access instructions as a 32-bit device.

BroadBahn™ Memory Architecture

The internal memory controller of the Z11 generates the timing parameters for display memory. It supports the DDRII SDRAM timing specifications

The frequency of the Volari™ Z11 memory controller interface is synchronous with the 2D engine at 125MHz with the I/O

interface at 250MHz. It can support up to a 1GB/s bandwidth, with a 16-bit DDRII SDRAM interface.

A DRAM capacity of 32MB is currently supported on cPCI-3920 boards.

VGA Analog Interface and Connector (CN3)

The 15-pin female connector CN3 is used to connect a VGA analog monitor to the cPCI-3920 board.

Signal Name	Pin #	Pin #	Signal Name
Red	1	2	Green
Blue	3	4	N.C.
GND	5	6	GND
GND	7	8	GND
+5V.	9	10	GND
N.C.	11	12	CRTDATA
HSYNC	13	14	VSYNC
CRTCLK	15		




Table 3-6: VGA Connector CN3 Pin Definition

Dual Gigabit Ethernet

The cPCI-3920 board includes two 10Base-T/100Base-TX/1000Base-T Ethernet ports based on the Dual Gigabit Ethernet controller, which is connected to the x4 PCI Express interfaces of the Intel® 3100.

The Intel® 82571EB Dual Gigabit Ethernet Controller's architecture is optimized to deliver high performance with the lowest power consumption. The controller's architecture includes independent transmit and receive queues and a PCI Express interface that maximizes the use of bursts for efficient bus usage.

The Boot from LAN feature is supported.




NOTE:

The Ethernet transmission can operate effectively using a CAT5 cable or higher specifications.

Gigabit Connector RJ-45 Pin Definitions (CN7/CN8)

The CN7/CN8 connector supplies the 10Base-T, 100Base-TX and 1000Base-T interfaces to the Ethernet controller.



10BASE--T		100BASE--TX		1000BASE--T		PIN
I/O	SIGNAL	I/O	SIGNAL	I/O	SIGNAL	
O	TX+	O	TX+	I/O	BI_DA+	1
O	TX-	O	TX-	I/O	BI_DA-	2
I	RX+	I	RX+	I/O	BI_DB+	3
--	--	--	--	I/O	BI_DC+	4
--	--	--	--	I/O	BI_DC-	5
I	TX--	I	RX--	I/O	BI_DB-	6
--	--	--	--	I/O	BI_DD+	7
--	--	--	--	I/O	BI_DD-	8

Table 3-7: Gigabit Connector CN7/CN8 Pin Definitions

Ethernet LED Status

SPEED (green):

When green it indicates a 1000BASE-TX connection. When not lit and the ACT-LED is active, the connection is operating at 100BASE-T.

ACT (yellow):

This LED monitors network connection and activity. The LED lights up when a valid link (cable connection) has been established. The LED goes temporarily off if network packets are being sent or received through the RJ-45 port. When this LED

remains off, a valid link has not been established due to a missing or a fault connection.

Status		Speed LED	Act LED
Network link is not established		OFF	OFF
10/100 Mbps	Link	OFF	ON
	Active	OFF	Blink
1000 Mbps	Link	ON	ON
	Active	ON	Blink

Table 3-8: Ethernet LED Status Definitions

Board-to-Board Connector

The 60-pin female Board-to-Board Connector (CN4) connects the main board to the DB-3920L2 daughter board, allowing I/O expansion and HDD connectivity for the cPCI-3920B 8HP version. The DB-3920L2 provides the following interfaces:

- ▶ Two USB2.0 ports
- ▶ Low pin count bus
- ▶ PS/2 Keyboard Mouse port
- ▶ SATA port with power
- ▶ XDP debug port

Legend for CN4 Pin Assignment

USBx	USB Interface and power
SATAx	Serial ATA port
LPCx	Low pin count interface
Kx, Mx	KB/MS port
XDPx BPMx Tx	XDP related signals

CN4 Pin Assignment

SIGNAL	PIN	PIN	SIGNAL
GND	1	2	LPC_FRAME#
USB3-D-	3	4	LPC_AD[3]
USB3-D+	5	6	LPC_AD[2]
GND	7	8	LPC_AD[1]
USB2_D-	9	10	LPC_AD[0]
USB2_D+	11	12	PCIRST
GND	13	14	CLK33
SATA0_RX-	15	16	GND
SATA0_RX+	17	18	+5V
GND	19	20	+5V
SATA0_TX+	21	22	+5V
SATA0_TX-	23	24	GND
GND	25	26	+3.3V
USB3_PWR	27	28	+3.3V
USB2_PWR	29	30	B2B_IN#
LPC_LDRQ0#	31	32	KB_CLK
A20GATE	33	34	KB_DAT
SERIRQ#	35	36	MS_CLK
KBD_RST#	37	38	MS_DAT
CPU_PWRGD	39	40	BPM[0]#
XDP_DBRESET#	41	42	BPM[1]#
TDI	43	44	BPM[2]#
TMS	45	46	BPM[3]#
TRST#	47	48	BPM[4]#
TCK	49	50	BPM[5]#
TDO	51	52	CPU_RST#
+1.05V	53	54	Reserved
+1.5V	55	56	Reserved
CLK100_ITP+	57	58	Reserved
CLK100_ITP-	59	60	Reserved

Table 3-9: Board-to-Board Connector Pin Definition

Keyboard/ Mouse Interface

The keyboard controller is located on the cPCI-3920B and is 8042 software compatible.

The PC/AT standard keyboard/mouse connector is a PS/2-type 6-pin shielded Mini-DIN connector.

A Y-cable to connect a mouse device and/or a keyboard to the PS/2 connector is included in the package of cPCI-3920B.

PS/2 Keyboard/Mouse Connector

Pin #	Signal	Function
1	KBDATA	Keyboard Data
2	MSDATA	Mouse Data
3	GND	Ground
4	+5V	Power
5	KBCLK	Keyboard Clock
6	MSCLK	Mouse Clock




Table 3-10: PS/2 Keyboard/Mouse Connector Pin Definition



NOTE:

The PS/2 power supply provides short-circuit protection and all the signal lines are EMI-filtered.

Universal Serial Ports

Two PC-compatible serial RS-232, 9-pin D-Sub ports are available and fully compatible with the 16C550 controller. These port includes a complete set of handshaking and modem control signals. Data transfer rates up to 115.2 kB/s are supported.

The COM3 interface is routed to the connector CN1.

COM3 DB-9 Serial Port Connector (CN1)

Pin #	RS-232
1	DCD, Data carrier detect
2	RXD, Receive data
3	TXD, Transmit data
4	DTR, Data terminal ready
5	GND, Ground
6	DSR, Data set ready
7	RTS, Request to send
8	CTS, Clear to send
9	RI, Ring indicator




Table 3-11: COM3 Serial Port Connector Pin Definition

The COM4 interface is routed to the connector CN6-2. The COM4 interface supports RS-232/422/485/485+.

COM4 DB-9 Serial Port Connector (CN6-2)

Pin #	RS-232	RS422/485+	RS485
1	DCD, Data carrier detect	TXD-	Data-
2	RXD, Receive data	TXD+	Data+
3	TXD, Transmit data	RXD+	--
4	DTR, Data terminal ready	RXD	--
5	IsoGND, Isolated ground	GND	GND
6	DSR, Data set ready	--	--
7	RTS, Request to send	--	--
8	CTS, Clear to send	--	--
9	RI, Ring indicator	--	--

Table 3-12: COM4 Serial Port Connector Pin Definition

COM4 Mode Switch Settings

	Location	SW1	SW2	SW3	SW4
RS232 Full Modem	1	ON	ON	OFF	ON
	2	OFF	OFF	OFF	OFF
	3	ON	ON	OFF	OFF
	4	OFF	OFF	OFF	OFF
RS422 Half Duplex	1	OFF	OFF	ON	OFF
	2	ON	ON	ON	ON
	3	OFF	OFF	OFF	OFF
	4	ON	ON	OFF	OFF
RS485 Half Duplex	1	OFF	OFF	ON	OFF
	2	ON	ON	ON	OFF
	3	OFF	OFF	OFF	ON
	4	ON	ON	OFF	OFF
RS485+ Half Duplex	1	OFF	OFF	OFF	OFF
	2	ON	ON	OFF	OFF
	3	OFF	OFF	ON	OFF
	4	ON	ON	ON	ON

Table 3-13: COM4 Mode Switch Settings


Serial ATA Interfaces

The cPCI-3920 provides up to four SATA interfaces. Three SATA ports, SATA1, SATA2 and SATA3, can be used only on the Rear Transition Module I/O interface. All SATA ports can be used simultaneously.

SATA Port	Connector	Usage
SATA0	CN3-2 on the cPCI-3920B	Onboard 2.5" DATA HDD drive mounted on CPCI-3920B
SATA1	CN5-R on the cPCI-R3920(T)	External SATA HDD drives, e.g. 2.5" or 3.5" SATA HDDs
SATA2	CN4-R on the cPCI-R3920(T)	External SATA HDD drives, e.g. 2.5" or 3.5" SATA HDDs
SATA3	CN2-R on the cPCI-R3920(T)	External SATA HDD drives, e.g. 2.5" or 3.5" SATA HDDs

The SATA connector, CN3-2, on the cPCI-3920B module is provided for connecting a 2.5" SATA HDD to the cPCI-3920B module. The SATA connector is divided into two segments, a signal segment and a power segment.

SATA0 Connector, CN3-2



SATA0 Connector, CN3-2

PIN	SIGNAL	FUNCTION	I/O
Signal Segment Key			
S1	GND	Ground signal	--
S2	SATA_TX2+	Differential Transmit+	O
S3	SATA_TX2-	Differential Transmit-	O
S4	GND	Ground signal	--
S5	SATA_RX2-	Differential Receive-	I
S6	SATA_RX2+	Differential Receive+	I
S7	GND	Ground signal	--
Signal Segment "L"			
Central Connector Polarizer			
Power Segment "L"			
P1	NC (3.3V)	Not connected	--
P2	NC (3.3V)	Not connected	--
P3	NC (3.3V)	Not connected	--
P4	GND	Ground signal	--
P5	GND	Ground signal	--
P6	GND	Ground signal	--
P7	5V	5V power	--
P8	5V	5V power	--
P9	5V	5V power	--
P10	GND	Ground signal	--
P11	RES	Reserved	--
P12	GND	Ground signal	--
P13	12V	12V power	--
P14	12V	12V power	--
P15	12V	12V power	--
Power Segment Key			

Table 3-14: SATA0 Connector Pin Definition

CompactPCI Bus Interfaces


The complete CompactPCI connector configuration comprises two connectors named J1 and J2. Their function is as follows:

- ▶ J1: 32-bit CompactPCI interface with PCI bus signals, arbitration, clock and power
- ▶ J2: has optional Rear I/O interface functionality or 64-bit termination

The board is capable of driving up to seven CompactPCI slots, with individual arbitration and clock signals. The cPCI-3920 is not hot-swappable but supports the addition or removal of other boards whilst in a powered-up state.

The cPCI-3920 is designed for a CompactPCI bus architecture. The CompactPCI standard is electrically identical to the PCI local bus. However, these systems are enhanced to operate in rugged industrial environments and to support multiple slots.

CompactPCI Connectors J1/J2



NOTE:

Pin rows F and Z are GND pins.

CompactPCI J1 Pin Assignment

Pin	Z	A	B	C	D	E	F
25	GND	+5V	REQ64#	ENUM#	+3.3V	+5V	GND
24	GND	AD[1]	+5V	V(I/O)	AD[0]	ACK64#	GND
23	GND	+3.3V	AD[4]	AD[3]	+5V	AD[2]	GND
22	GND	AD[7]	GND	+3.3V	AD[6]	AD[5]	GND
21	GND	+3.3V	AD[9]	AD[8]	M66EN(2)	C/ BE[0]#	GND
20	GND	AD[12]	GND	V(I/O)	AD[11]	AD[10]	GND
19	GND	+3.3V	AD[15]	AD[14]	GND	AD[13]	GND
18	GND	SERR#	GND	+3.3V	PAR	C/ BE[1]#	GND
17	GND	+3.3V	N.C.	N.C.	GND	PERR#	GND
16	GND	DEVSEL#	GND	V(I/O)	STOP#	LOCK#	GND
15	GND	+3.3V	FRAME#	IRDY#	GND	TRDY#	GND
12-14	GND	Key					GND
11	GND	AD[18]	AD[17]	AD[16]	GND	C/ BE[2]#	GND
10	GND	AD[21]	GND	+3.3V	AD[20]	AD[19]	GND
9	GND	C/BE[3]#	GND	AD[23]	GND	AD[22]	GND
8	GND	AD[26]	GND	V(I/O)	AD[25]	AD[24]	GND
7	GND	AD[30]	AD[29]	AD[28]	GND	AD[27]	GND
6	GND	REQ0#	GND	+3.3V	CLK0	AD[31]	GND
5	GND	N.C.	N.C.	PCIRST#	GND	GNT[0]#	GND
4	GND	IPMB_PWR	GND	V(I/O)	INTP(1)	INTS	GND
3	GND	INTA#	INTB#	INTC#	+5V	INTD#	GND
2	GND	TCK	+5V	TMS	TDO	TDI	GND
1	GND	+5V	-12V	TRST#(3)	+12V	+5V	GND
	Z	A	B	C	D	E	F

Table 3-15: CompactPCI J1 Pin Assignment

CompactPCI J2 Pin Assignment

The cPCI-3920 board provides Rear I/O connectivity for special compact systems. Some standard PC interfaces are implemented and assigned to the front panel and to the rear connector J2.

When the Rear I/O module is used, the signals of some of the main board/front panel connectors are routed to the Rear I/O module interface. Thus the Rear I/O module makes it much easier to remove the CPU in the rack as there is practically no cabling on the CPU board.

For the system Rear I/O feature a special backplane is necessary. The cPCI-3920 with Rear I/O is compatible with all standard CompactPCI passive backplanes with Rear I/O support on the system slot.

The cPCI-3920 Rear I/O provides the following interfaces:

- ▶ 32-bit/33 MHz CompactPCI (J1) and Rear I/O (J2)
- ▶ Two USB 2.0 ports
- ▶ Two Gigabit Ethernet ports without LED signals
- ▶ Three SATA ports
- ▶ Two COM ports
- ▶ Seven GPIOs



NOTE:

To support the Rear I/O feature a special backplane is necessary. Do not plug a Rear I/O configured board in a non-system slot Rear I/O backplane. Failure to comply with the above will result in damage to your board.

Legend for J2 Pin Assignment

USB_x	USB interface and power
ETH_x	Gigabit Ethernet port
SATA_x	Serial ATA port
COM_x	COM port
GPIO_x	GPIO
PEX_RX0L_x	1 x4 or 4 x1 PCI-Express
PEX_TX0L_x	

Pin	Z	A	B	C	D	E	F
22	N.C	GA[4]	GA[3]	GA[2]	GA[1]	GA[0]	GND
21	N.C	CLK[6]	GND	COM1_RXD	COM2_RXD	GPIO7	GND
20	N.C	CLK[5]	GND	COM1_TXD	COM2_TXD	GPIO6	GND
19	N.C	GND/CLK100+	GND/CLK100+	SMB_SDA	SMB_SCL	SMB_ALERT	GND
18	N.C	SATA3_TX+	SATA3_TX-	GND	SATA3_RX+	SATA3_RX-	GND
17	N.C	USB4_D+	USB4_D	RST_BP#	N.C.	GNT[6]#pull	GND
16	N.C	USB4_PWR	USB5_PWR	DEGXB	GND	GPIO5	GND
15	N.C	USB5_D+	USB5_D	FALXB	N.C.	GNT[5]#pull	GND
14	N.C	SATA2_TX+	SATA2_TX-	GND	SATA2_RX+	SATA2_RX-	GND
13	N.C	SATA1_TX+	SATA1_TX-	GND	SATA1_RX+	SATA1_RX-	GND
12	N.C	PEX_RX0L0+	PEX_RX0L0-	GND	PEX_TX0L0	PEX_TX0L0-	GND
11	N.C	PEX_RX0L1+	PEX_RX0L1-	GND	PEX_TX0L1	PEX_TX0L1-	GND
10	N.C	PEX_RX0L2+	PEX_RX0L2-	GND	PEX_TX0L2	PEX_TX0L2-	GND
9	N.C	PEX_RX0L3+	PEX_RX0L3-	GND	PEX_TX0L3	PEX_TX0L3-	GND
8	N.C	ETH0_DA+	ETH0_DA-	GND	ETH0_DC+	ETH0_DC-	GND
7	N.C	ETH0_DB+	ETH0_DB-	GND	ETH0_DD+	ETH0_DD-	GND
6	N.C	ETH1_DA+	ETH1_DA-	GND	ETH1_DC+	ETH1_DC-	GND
5	N.C	ETH1_DB+	ETH1_DB-	GND	ETH1_DD+	ETH1_DD-	GND
4	N.C	V(I/O)	GPIO1	GPIO2	GPIO3	GPIO4	GND
3	N.C	CLK[4]	GND	GNT[3]#	N.C.	GNT[4]#pull	GND
2	N.C	CLK[2]	CLK[3]	SYSEN#	GNT[2]#	REQ[3]#	GND
1	N.C	CLK[1]	GND	REQ[1]#	GNT[1]#	REQ[2]#	GND

Table 3-16: CompactPCI J2 Pin Assignment

3.4 Board Interfaces on RTM

There are two identical USB interfaces on the CPCI-R3920(T) RTM, each with a maximum transfer rate of 480 Mb/s provided for connecting USB devices. One USB peripheral may be connected to each port. To connect more USB devices than there are available ports, an external hub is required.

USB Connectors CN7-R and CN8-R

Pin #	Signal Name
1	Vcc
2	UV0-
3	UV0+
4	GND




Table 3-17: RTM USB Connector Pin Definitions



NOTE:

The CPCI-R3920(T) host interfaces can be used with maximum 500 mA continuous load current as specified in the Universal Serial Bus Specification, Revision 2.0. Short-circuit protection is provided. All the signal lines are EMI-filtered. The Rear I/O interface supports the USB 1.1 and USB 2.0 standards. For USB 2.0 it is strongly recommended to use a cable length not exceeding 3 meters.

Gigabit Ethernet Interfaces

Gigabit Ethernet signals are available either on the front R-J45 connector or on the Rear I/O interface due to the implemented switches on the cPCI-3920. Both Gigabit Ethernet channels are individually switchable to front or Rear I/O. Switching over from front to Rear I/O or vice versa is effected using the BIOS settings or the board-specific registers (default: front I/O). For further information on the BIOS settings, refer to Chapter BIOS.

The interfaces provide automatic detection and switching between 10Base-T, 100Base-TX and 1000Base-T data transmission (Auto-Negotiation).

The CN6-R connector supplies the 10Base-T, 100Base-TX and 1000Base-T interfaces to the Ethernet controller.

Gigabit Connector RJ-45 Pin Definitions (CN6-R)

The CN7/CN8 connector supplies the 10Base-T, 100Base-TX and 1000Base-T interfaces to the Ethernet controller.

10BASE--T		100BASE--TX		1000BASE--T		PIN
I/O	SIGNAL	I/O	SIGNAL	I/O	SIGNAL	
O	TX+	O	TX+	I/O	BI_DA+	1
O	TX-	O	TX-	I/O	BI_DA-	2
I	RX+	I	RX+	I/O	BI_DB+	3
--	--	--	--	I/O	BI_DC+	4
--	--	--	--	I/O	BI_DC-	5
I	TX--	I	RX--	I/O	BI_DB-	6
--	--	--	--	I/O	BI_DD+	7
--	--	--	--	I/O	BI_DD-	8

Table 3-18: RTM Gigabit Connector Pin Definitions



NOTE:

The Ethernet transmission can operate effectively using a CAT5 cable or higher specifications.

COM1 and COM2 Interfaces

The CPCI-R3920(T) provides two COM ports from the Intel® 3100 chipset for connecting RS-232 devices to the CPCI-R3920(T).

The following tables provide pinout information for the 9-pin D-Sub COM connector CN3-R located on the front panel and the onboard COM connector CN1-R.

COM1 DB-9 Serial Port Connector (CN3-R)

Pin #	RS-232
1	not used
2	RXD, Receive data
3	TXD, Transmit data
4	not used
5	GND, Ground
6	not used
7	not used
8	not used
9	not used




Table 3-19: COM1 Serial Port Connector Pin Definition

COM2 Onboard Serial Port Connector (CN1-R)

Pin #	RS-232
1	not used
2	not used
3	RXD, Receive data
4	not used
5	TXD, Transmit data
6	not used
7	not used
8	not used
9	GND, Ground
10	NC




Table 3-20: COM2 Serial Port Connector Pin Definition



NOTE:


The serial ports of Intel® 3100 Chipset are not 100 percent compatible with other 16550 standard devices. If any system or software designer assumes that they are compatible with other 16550 standard devices and does not follow the specifications for the Serial I/O Unit in the **Intel® 3100 Chipset Datasheet**, errors or undesired behaviors may be observed.

Serial ATA Interfaces - SATA1-3

The onboard Serial ATA connectors CN2-R, CN4-R and CN5-R allow the connection of standard HDDs and other Serial ATA devices to the cPCI-3920 Rear Transition Module.

The following figure and table provide pinout information for the SATA connectors CN2-R, CN4-R and CN5-R.

SATA1-3 Connectors CN2-R, CN4-R and CN5-R



Pin #	Signal	Pin #	Signal
1	GND	5	RX-
2	TX+	6	RX+
3	TX-	7	GND
4	GND		


Table 3-21: SATA1-3 Connectors Pin Definition

Rear I/O Interfaces on CompactPCI Connector rJ2

The cPCI-3920 Rear Transition Module conducts a wide range of I/O signals through the Rear I/O connector rJ2.

To support the Rear I/O feature a special backplane is necessary. Do not plug a Rear I/O configured board in a non-system slot Rear I/O backplane. Failure to comply with the above may result in damage to your board.

CompactPCI Connector rJ2



CompactPCI rJ2 Pin Assignment

Legend for rJ2 Pin Assignment

USBx	USB interface and power
ETHx	Gigabit Ethernet port
SATAx	Serial ATA port
COMx	COM port

Pin	Z	A	B	C	D	E	F
22	N.C.	GA[4]	GA[3]	GA[2]	GA[1]	GA[0]	GND
21	N.C.	CLK[6]	GND	COM1_RXD	COM2_RXD	N.C.	GND
20	N.C.	CLK[5]	GND	COM1_TXD	COM2_TXD	N.C.	GND
19	N.C.	GND/CLK100	GND/CLK100	SMB_SDA	SMB_SCL	SMB_ALERT	GND
18	N.C.	SATA3_TX+	SATA3_TX-	GND	SATA3_RX+	SATA3_RX-	GND
17	N.C.	USB4_D+	USB4_D	RST_BP#	N.C.	GNT[6]#pull	GND
16	N.C.	USB4_PWR	USB5_PWR	DEGXB	GND	GPIO5	GND
15	N.C.	USB5_D+	USB5_D	FALXB	N.C.	GNT[5]#pull	GND
14	N.C.	SATA2_TX+	SATA2_TX-	GND	SATA2_RX+	SATA2_RX-	GND
13	N.C.	SATA1_TX+	SATA1_TX-	GND	SATA1_RX+	SATA1_RX-	GND
12	N.C.	N.C.	N.C.	GND	N.C.	N.C.	GND
11	N.C.	N.C.	N.C.	GND	N.C.	N.C.	GND
10	N.C.	N.C.	N.C.	GND	N.C.	N.C.	GND
9	N.C.	N.C.	N.C.	GND	N.C.	N.C.	GND
8	N.C.	ETH0_DA+	ETH0_DA-	GND	ETH0_DC+	ETH0_DC-	GND
7	N.C.	ETH0_DB+	ETH0_DB-	GND	ETH0_DD+	ETH0_DD-	GND
6	N.C.	ETH1_DA+	ETH1_DA-	GND	ETH1_DC+	ETH1_DC-	GND
5	N.C.	ETH1_DB+	ETH1_DB-	GND	ETH1_DD+	ETH1_DD-	GND
4	N.C.	V(I/O)	N.C.	N.C.	N.C.	N.C.	GND
3	N.C.	CLK[4]	GND	GNT[3]#	N.C.	GNT[4]#pull	GND
2	N.C.	CLK[2]	CLK[3]	SYSEN#	GNT[2]#	REQ[3]#	GND
1	N.C.	CLK[1]	GND	REQ[1]#	GNT[1]#	REQ[2]#	GND

Table 3-22: CompactPCI rJ2 Pin Assignment

4 Getting Started

The cPCI-3920 has been designed for easy installation. However, the following standard precautions, installation procedures, and general information must be observed to ensure proper installation and to preclude damage to the board, other system components, or injury to personnel.

4.1 Safety Requirements

The following safety precautions must be observed when installing or operating the cPCI-3920. ADLINK assumes no responsibility for any damage resulting from failure to comply with these requirements.

Exercised due care when handling the board as the heat sink can get very hot. Do not touch the heat sink when installing or removing the board. The board should not be placed on any surface or in any form of storage container until the board and heat sink have cooled down to room temperature.

If your board type is not specifically qualified as being hot swap capable, switch off the CompactPCI system power before installing the board in a free CompactPCI slot. Failure to do so could endanger your life or health and may damage your board or system.

Certain CompactPCI boards require bus master and/or Rear I/O capability. If you are in doubt whether such features are required for the board you intend to install, please check your specific board and/or system documentation to make sure that your system is provided with an appropriate free slot in which to insert the board.


This CompactPCI board contains electrostatically sensitive devices. Please observe the necessary precautions to avoid damage to your board:

- ▶ Discharge your clothing before touching the assembly. Tools must be discharged before use.
- ▶ Do not touch components, connector-pins or traces.
- ▶ If working at an anti-static workbench with professional discharging equipment, please do not omit to use it.

4.2 Installing the USB Flash Disk

The cPCI-3920 supports an onboard USB Flash Disk module via the CN5 pin header. To install a USB Flash Disk, follow the procedure below.

1. Secure the standoff to the underside of the module with the screw provided.
2. Align the module with the CN5 pin header and mounting hole as shown.



3. Insert the module onto the pin header and secure with the screw provided from the back side of the cPCI-3920.



4.3 Installing the Hard Disk Drive (cPCI-3290B only)


The cPCI-3920B supports a slim-type 2.5" SATA HDD. If the cPCI-3920 comes with a pre-installed HDD, proceed to the next section.

To install the hard disk drive:

1. Place the HDD into the bracket as shown.



2. Insert the the HDD into the CN3-2 SATA signal/power connector.



3. Tighten all four bracket screws to secure the HDD in place.

4.4 Installing the cPCI-3920 to the Chassis

To install the cPCI-3920 module to a CompactPCI chassis:

1. Refer to the chassis documentation before installing the cPCI-3920.
2. Turn off the power in both chassis front and rear.
3. Assign a system slot for the board. Make sure you assign the correct slot.
4. Remove the panel cover of the slot you have selected.
5. Remove the black plastic caps securing the mounting screws to the front panel.
6. Align the top and bottom edges of the board with the card guides on the chassis, then push the board until it is completely flushed on the chassis.
7. Move the locking handle inward until it is fully-latched. A slight resistance may be felt when inserting the board. If the resistance is too strong, check if there are bent pins on the backplane or if the board's connector pins are properly aligned with the connectors on the backplane.
8. Check if the board is seated properly on the slot. Secure the board with mounting screws (behind the upper and lower ejector)
9. Connect the cables and peripherals to the board, then turn the chassis on.

4.5 RTM (cPCI-R3920) Installation

Follow the typical cPCI board installation and removal procedures for the RTM. However, be careful when inserting or removing RTMs to the chassis as these are shorter than front boards.

Refer to previous sections when connecting or installing peripherals to the RTM. Make sure that the RTMs you are installing are compatible with the cPCI-3920 Series.



NOTE:

You must install the correct RTM to enable some functionalities (I/O interfaces) on the rear panel. Installation of non-compatible RTMs may damage the system board and/or other RTMs.

4.6 Hot Swap Procedures

The cPCI-3920 is not designed for hot swap operation. Do not attempt to hot swap this board. However, the cPCI-3920 supports the addition or removal of other boards whilst in a powered-up state.

This page intentionally left blank.

5 Driver Installation

The cPCI-3920 drivers are available from the ADLINK All-In-One CD at **X:\cPCI\cPCI-3920**, or from the ADLINK website (<http://www.adlinktech.com>). The following describes the driver installation procedures for Windows® 2000, Windows® XP or Windows® Server 2003:

1. Install the Windows operating system before installing any driver. Most standard I/O device drivers are installed during Windows installation.
2. Install the chipset driver by running the program **...\Chipset\Inflnst_AUTOL.exe**.
3. Install the VGA driver and utilities by running the program **...\VGA\IR1.09.05_WHQL_Windows\XGIRun.exe**.
4. Install the LAN drivers by running the program **...\LAN\PRO2KXP.exe**.

We recommend using the chipset, VGA, and LAN drivers provided on the ADLINK All-in-One CD or downloaded from the ADLINK website to ensure compatibility. Contact ADLINK to get support for Linux and VxWorks BSP drivers.

This page intentionally left blank.

6 Watchdog Timer

6.1 WDT Overview

This section explains the operation of the cPCI-3920's Watchdog Timer (WDT). The primary function of the WDT is to monitor the cPCI-3920 operation and to reset the system if a software application fails to function as programmed. The following WDT functions may be controlled using a software application:

- ▶ enabled and disabled
- ▶ reloading timeout value




Figure 6-1: cPCI-3920 Watchdog Timer Architecture

The cPCI-3920 implements the internal WDT unit of the Intel 3100 chipset and its LPC interface. It contains registers of device6 at

the internal IO to control the WDT and retrieve its status. The basic functions of the WDT include:

- ▶ Setting the watchdog timeout interval
- ▶ Starting the timer countdown
- ▶ Selecting 1 step or 2 step WDT
- ▶ Enabling or disabling WDT
- ▶ Reloading the timeout value to keep the watchdog from timing out
- ▶ Setting the range of the timeout period from 1 μ s to 1 second, or from 1 ms to 1050 seconds

When the watchdog times out, it will send a RESET signal to the system.

6.2 Using the Watchdog Timer in an Application

The following section describes the WDT functions in an application. The WDT reset function is explained in the previous section. This can be controlled through the registers in the WDT unit of the Intel 3100 chipset .

An application using the reset feature enables the watchdog function, sets the count-down period, and reloads the timeout value periodically to keep it from resetting the system. If the timer count-down value is not reloaded, the watchdog resets the system hardware after its counter registers zero.

A detailed programming sample is provided below:

```
#include<dos.h>
#include<conio.h>
#include<stdio.h>
#include<stdlib.h>

#defineconfig_port_index0x4E
#defineconfig_port_data0x4F

/* Pre-declaration */
/* access configuration registers routines */
void enter_config_mode();
void exit_config_mode();
```

```

void write_config_data_byte(unsigned
    char,unsigned char);
unsigned char read_config_data_byte(unsigned
    char);
unsigned int read_wdt_io_base();
/* access wdt I/O registers routines */
void write_preload_val2_reg(unsigned long int);
void clear_preload_val1_reg();
void unlocking_reg();

/* Global parameter */
unsigned int wdt_io_base;

void main(void)
{
    //    unsigned int wdt_io_base;
    unsigned long int time_out_val=0;

    wdt_io_base=read_wdt_io_base();

    printf("Intel 3100 Chipset Watch-Dog Timer
    test utility.\n");
    printf("Intel 3100 WDT IO Base Address ==
    0x%x\n",wdt_io_base);

    while(1)//
        (time_out_val==0)|| (time_out_val>1050))
        {
            //3sec    printf("Please input the time to count
            down (1-1050 sec): ");
            //3sec    scanf("%d",&time_out_val);
        }

    //3sec time_out_val=time_out_val*1000;//transfer
        to msec unit.
        time_out_val=time_out_val+3000;    //3sec
        clear_preload_val1_reg();//we don't need
        preload_val1 caused internal interrupt.

        write_preload_val2_reg(time_out_val);//
        write preload_val2 ,it will cause external
        interrupt.(WDT_TOUT#)

```

```

    outportb(wdt_io_base+0x18,2);//watchdog
    timer enable!!

    printf("\nPlease waiting for Watch-Dog Timer
    time-out!!");
}
/*****/
unsigned int read_wdt_io_base()
{
    unsigned char_wdt_io_base[2];
    int *p_wdt_io_base;
    p_wdt_io_base=&_wdt_io_base;

    enter_config_mode();

    write_config_data_byte(0x07,6);//select
    logic 6 - WDT

    _wdt_io_base[1]=read_config_data_byte(0x60)
    ;

    _wdt_io_base[0]=read_config_data_byte(0x61)
    ;

    exit_config_mode();

    return (*p_wdt_io_base);
}
/*****/
void enter_config_mode()
{
    outportb(config_port_index,0x80);

    outportb(0xeb,00); //io delay

    outportb(config_port_index,0x86);
}
/*****/
void exit_config_mode()
{
    outportb(config_port_index,0x68);
}

```



```

        outportb(0xeb,00); //io delay

        outportb(config_port_index,0x08);
    }
    /*****/
    unsigned char read_config_data_byte(unsigned char
        _index)
    {
        unsigned char r_data;

        outportb(config_port_index,_index);

        outportb(0xeb,00); //io delay

        r_data=inportb(config_port_data);

        return(r_data);
    }
    /*****/
    void write_config_data_byte(unsigned char
        _index,unsigned char _data)
    {
        outportb(config_port_index,_index);

        outportb(0xeb,00); //io delay

        outportb(config_port_data,_data);
    }
    /*****/
    void write_preload_val2_reg(unsigned long int
        _time_out_val)
    {
        unsigned char *p_data;
        // "unsigned char" declaration --> p_data++ =
        // addr. BYTE increased.
        p_data=&_time_out_val;
        // printf("%x\n", *p_data);

        unlocking_reg();
        outportb(wdt_io_base+4, *p_data);
        p_data++;
        // printf("%x\n", *p_data);
    }

```

```
        unlocking_reg();
        outportb(wdt_io_base+5, *p_data);
        p_data++;
    //    printf("%x\n", *p_data);

        unlocking_reg();
        outportb(wdt_io_base+6, *p_data);
    }
    /*****/
void clear_preload_val1_reg()
{
    unlocking_reg();
    outportb(wdt_io_base, 0x00);

    unlocking_reg();
    outportb(wdt_io_base+1, 0x00);

    unlocking_reg();
    outportb(wdt_io_base+2, 0x00);

}
/*****/
void unlocking_reg()
{
    outportb(wdt_io_base+12, 0x80);

    outportb(0xeb, 00); //io delay

    outportb(wdt_io_base+12, 0x86);
```

7 BIOS Setup Utility

The following chapter describes basic navigation for the AMIBIOS®8 BIOS setup utility.

7.1 Starting the BIOS

To enter the setup screen, follow these steps:

1. Power on the motherboard
2. Press the < Delete > key on your keyboard when you see the following text prompt:
< Press DEL to run Setup >
3. After you press the < Delete > key, the main BIOS setup menu displays. You can access the other setup screens from the main BIOS setup menu, such as Chipset and Power menus.



NOTE:


In most cases, the < Delete > key is used to invoke the setup screen. There are several cases that use other keys, such as < F1 >, < F2 >, and so on.

Setup Menu

The main BIOS setup menu is the first screen that you can navigate. Each main BIOS setup menu option is described in this user's guide.

The Main BIOS setup menu screen has two main frames. The left frame displays all the options that can be configured. "Grayed" options cannot be configured, "Blue" options can be.


The right frame displays the key legend. Above the key legend is an area reserved for a text message. When an option is selected in the left frame, it is highlighted in white. Often a text message will accompany it.



Navigation

The BIOS setup/utility uses a key-based navigation system called hot keys. Most of the BIOS setup utility hot keys can be used at any time during the setup navigation process.

These keys include < F1 >, < F10 >, < Enter >, < ESC >, < Arrow > keys, and so on. .



NOTE:


There is a hot key legend located in the right frame on most setup screens.

The < F8 > key on your keyboard is the Fail-Safe key. It is not displayed on the key legend by default. To set the Fail-Safe settings of the BIOS, press the < F8 > key on your keyboard. It is located on the upper row of a standard 101 keyboard. The Fail-Safe settings allow the motherboard to boot up with the least amount of options set. This can lessen the probability of conflicting settings.


Hotkey Descriptions

F1 The < F1 > key allows you to display the General Help screen.

Press the < F1 > key to open the General Help screen.




- F10** The < F10 > key allows you to save any changes you have made and exit Setup. Press the < F10 > key to save your changes. The following screen will appear:



Press the < Enter > key to save the configuration and exit. You can also use the < Arrow > key to select Cancel and then press the < Enter > key to abort this function and return to the previous screen.

- ESC** The < Esc > key allows you to discard any changes you have made and exit the Setup. Press the < Esc > key to exit the setup without saving your changes. The following screen will appear:



Press the < Enter > key to discard changes and exit. You can also use the < Arrow > key to select Cancel and then press the < Enter > key to abort this function and return to the previous screen.

- Enter** The < Enter > key allows you to display or change the setup option listed for a particular setup item. The < Enter > key can also allow you to display the setup sub-screens.

7.2 Main Setup

When you first enter the Setup Utility, you will enter the Main setup screen. You can always return to the Main setup screen by selecting the Main tab. The Main BIOS Setup screen is shown below.

BIOS SETUP UTILITY	
Main	Advanced PCIPnP Boot Security Chipset Exit
System Overview	
AMIBIOS Version :08.00.14 Build Date:08/26/10 ID :C3920B32	
Processor Speed :255MHz Count :255	
System Memory Size :1024MB	
System Time [00:00:51] System Date [Tue 01/01/2002]	
▶ Input UUID	
Use [ENTER], [TAB] or [SHIFT-TAB] to select a field. Use [+] or [-] to configure system Date. + Select Screen ↑↓ Select Item +- Change Field Tab Select Field F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

System Time/System Date

Use this option to change the system time and date. Highlight System Time or System Date using the < Arrow > keys. Enter new values using the keyboard. Press the < Tab > key or the < Arrow > keys to move between fields. The date must be entered in MM/DD/YY format. The time is entered in HH:MM:SS format.



NOTE:

The time is in 24-hour format. For example, 5:30 A.M. appears as 05:30:00, and 5:30 P.M. as 17:30:00.

Input UUID

Use this function to set a unique Universally Unique Identifier (UUID) for the system.

Main	
UUID Configuration	
WARNING: The UUID will be updated after boot.	
System UUID : A4E399AE8DF5ADFBBF4D4F2FA35F70AE1	
UUID Byte 0-7	[]
UUID Byte 8-F	[]
← Select Screen ↑↓ Select Item F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

UUID Byte 0-7

This field sets bytes 0-7 of the UUID.


UUID Byte 8-F

This field sets bytes 8-F of the UUID.

7.3 Advanced BIOS Setup

Select the Advanced tab from the setup screen to enter the Advanced BIOS Setup screen. You can select any of the items in the left frame of the screen to go to the sub menu for that item. You can display an Advanced BIOS Setup option by highlighting it using the < Arrow > keys. The Advanced BIOS Setup screen is shown below.

The sub menus are described on the following pages.



CPU Configuration

You can use this screen to select options for the CPU Configuration Settings. Use the up and down < Arrow > keys to select an item. Use the < + > and < - > keys to change the value of the selected option. A description of the selected item appears on the right side of the screen. The settings are described on the following pages. CPU Configuration screens for the available CPUs are shown below.

Intel® Core™2 Duo L7400

BIOS SETUP UTILITY	
Advanced	
Configure advanced CPU settings Module Version:3F.02	
Manufacturer: Intel	
Frequency : 255MHz FSB Speed : 113MHz Cache L1 : 0 KB Cache L2 : 0 KB Ratio Actual Value: 9	
Hardware Prefetcher	[Enabled]
Adjacent Cache Line Prefetch	[Enabled]
Intel(R) Virtualization Tech	[Enabled]
Intel(R) SpeedStep(tm) tech	[Enabled]
ACPI T-STATE tech	[Enabled]
This should be enabled in order to enable or disable the Hardware Prefetcher Disable Feature.	
← Select Screen ↑↓ Select Item +− Change Option F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

Hardware Prefetcher

The processor has a hardware prefetcher that automatically analyzes its requirements and prefetches data and instructions from the memory into the Level 2 cache that are likely to be required in the near future. This reduces the latency associated with memory reads.

When **Enabled**, the processor's hardware prefetcher will be enabled and allowed to automatically prefetch data and code for the processor. When **Disabled**, the processor's hardware prefetcher will be disabled.

Adjacent Cache Line Prefetch

The processor has a hardware adjacent cache line prefetch mechanism that automatically fetches an extra 64-byte cache line whenever the processor requests for a 64-byte cache line.

This reduces cache latency by making the next cache line immediately available if the processor requires it as well.

When **Enabled**, the processor will retrieve the currently requested cache line, as well as the subsequent cache line. When **Disabled**, the processor will only retrieve the currently requested cache line.

Intel® Virtualization Technology

This option is used to enable or disable the Intel® Virtualization Technology (IVT) extension, which is also known by the development code name of Vanderpool. It allows multiple operating systems to run simultaneously on the same system. It does this by creating virtual machines, each running its own x86 operating system. When **Enabled**, the IVT extensions will be enabled, allowing for hardware-assisted virtual machine management. When **Disabled**, the IVT extensions will be disabled. However, software virtual machine managers like VMware can still be used if virtualization is required.

Intel® SpeedStep™ Technology

Allows you to **Enable** or **Disable** Intel® SpeedStep™ Technology. If SpeedStep is disabled, the **CPU Frequency on XP/Linux** option will become visible.

Hardware Prefetcher	[Enabled]	
Adjacent Cache Line Prefetch	[Enabled]	← Select Screen
Intel(R) Virtualization Tech	[Enabled]	↑↓ Select Item
Intel(R) SpeedStep(tm) tech	[Disabled]	+− Change Option
ACPI T-STATE tech	[Enabled]	F1 General Help
CPU Frequency on XP/Linux	[1500MHz]	F10 Save and Exit
		ESC Exit

v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.

ACPI T-State Tech

This option allows you to **Enable** or **Disable** ACPI throttling.

CPU Frequency on XP/Linux

This option is used to manually set the CPU frequency on XP and Linux operating systems. The following options are available: 1500MHz, 1333MHz, 1166MHz, and 1000MHz.

Intel® Core™ Duo U2500

BIOS SETUP UTILITY	
Advanced	
Configure advanced CPU settings Module Version:3F.02 Manufacturer: Intel Frequency :255MHz FSB Speed :113MHz Cache L1 :0 KB Cache L2 :0 KB Ratio Actual Value:9 Intel(R) Virtualization Tech [Enabled] Intel(R) SpeedStep(tm) tech [Enabled]	Disable: Disable GV3 Enable: Enable GV3 ← Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	


Intel® Virtualization Technology

This is used to enable or disable the Intel® Virtualization Technology (IVT) extension, which is also known by the development code name of Vanderpool. It allows multiple operating systems to run simultaneously on the same system. It does this by creating virtual machines, each running its own x86 operating system. When **enabled**, the IVT extensions will be enabled, allowing for hardware-assisted virtual machine management. When **disabled**, the IVT extensions will be disabled. However, software virtual machine managers like VMware can still be used if virtualization is required.

Intel® SpeedStep™ Technology

This allows you to **enable** or **disable** Intel® SpeedStep™ Technology.

Intel® Celeron® M ULV 423



IDE Configuration

You can use this screen to select options for the IDE Configuration Settings. Use the up and down < Arrow > keys to select an item. Use the < + > and < - > keys to change the value of the selected option. A description of the selected item appears on the right side of the screen. The settings are described on the following pages. An example of the IDE Configuration screen is shown below.

BIOS SETUP UTILITY	
Advanced	
IDE Configuration ATA/IDE Configuration Configure SATA as ▶ Primary IDE Master ▶ Primary IDE Slave ▶ Secondary IDE Master ▶ Secondary IDE Slave Hard Disk Write Protect IDE Detect Time Out (Sec) [Enhanced] [IDE] : [Not Detected] : [Not Detected] : [Not Detected] : [Not Detected] [Disabled] [35]	
Select whether the IDE channels should be initialized in Compatible or Enhanced mode of operation. ← Select Screen ↑↓ Select Item + - Change Option F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

ATA/IDE Configuration

This item specifies whether the IDE channels should be initialized in Compatible or Enhanced mode of operation. The settings are **Disabled**, **Compatible** and **Enhanced**.

Configure SATA as

This item specifies SATA channels transport to what kind of channels. The settings are **IDE mode** and **AHCI mode**.

Primary IDE Master, Primary IDE Slave, Secondary IDE Master, Secondary IDE Slave

Select one of the hard disk drives to configure it. Press < Enter > to access its sub menu.

Hard Disk Write Protect


This will be effective only if device is accessed through BIOS. The settings are **Enabled** and **Disabled**.

IDE Detect Time Out (Sec)

Select the time out value for detecting ATA/ATAPI devices. The settings are **0 sec**, **5 sec**, **10 sec**, **15 sec**, **20 sec**, **25sec**, **30 sec**, and **35 sec**.

AHCI Configuration

While entering setup BIOS auto detects the presence of IDE devices.



Hardware Health Configuration

This option displays the current status of all of the monitored hardware devices / components such as voltages and temperatures.

BIOS SETUP UTILITY	
Advanced	
System Hardware Health	
CPU Temperature	:39°C/102°F
System Temperature	:12°C/53°F
VCORE	:0.964 V
VIN0 (+3.3V)	:3.340 V
VIN1 (+1.8V)	:1.824 V
VIN2 (+1.5V)	:1.532 V
VIN3 (+12v)	:11.976 V
VCC	:4.890 V
5VSB	:4.848 V
VBAT	:3.328 V
← Select Screen ↑↓ Select Item F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

Remote Access Configuration

Remote Access Configuration provides the settings to allow remote access by another computer to get POST messages and send commands through serial port access.

BIOS SETUP UTILITY	
Advanced	
Configure Remote Access type and parameters	
Remote Access	[Enabled]
Serial port number	[COM1]
Base Address, IRQ	[3F8h, 4]
Serial Port Mode	[115200 8,n,1]
Flow Control	[None]
Redirection After BIOS POST	[Always]
Terminal Type	[ANSI]
UT-UTF8 Combo Key Support	[Enabled]
Sredir Memory Display Delay	[No Delay]
Select Remote Access type. + Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit	
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

Remote Access

Select this option to **Enabled** or **Disabled** the BIOS remote access feature.

Serial Port Number

Select the serial port you want to use for the remote access interface. You can set the value for this option to either **COM1** or **COM2**. The Base Address and IRQ of the selected serial port is displayed.

Serial Port Mode

Select the baud rate you want the serial port to use for console redirection. The options are **115200 8,n,1**; **57600 8,n,1**; **19200 8,n,1**; and **09600 8,n,1**.

Flow Control

Set this option to select Flow Control for console redirection. The settings for this value are **None**, **Hardware**, or **Software**.

Terminal Type

This option is used to select either VT100/VT-UTF8 or ANSI terminal type. The settings for this value are **ANSI**, **VT100**, or **VT-UTF8**.

VT-UTF8 Combo Key Support


This option enables VT-UTF8 Combination Key Support for ANSI/VT100 terminals. The settings for this value are **Enabled** or **Disabled**.

Sredir Memory Display Delay

This option gives the delay in seconds to display memory information. The options for this value are No Delay, Delay 1 Sec, Delay 2 Sec, or Delay 4 Sec.

USB Configuration

You can use this screen to select options for the USB Configuration. Use the up and down < Arrow > keys to select an item. Use the < + > and < - > keys to change the value of the selected option. The settings are described on the following pages. The screen is shown below.



Legacy USB Support

Legacy USB Support refers to USB mouse and keyboard support. Normally if this option is not enabled, any attached USB mouse or USB keyboard will not become available until a USB compatible operating system is fully booted with all USB drivers loaded. When this option is enabled, any attached USB mouse or USB keyboard can control the system even when there are no USB drivers loaded on the system. Set this value to enable or disable Legacy USB Support.

Disabled Set this value to prevent the use of any USB device in DOS or during system boot.

Enabled Set this value to allow the use of USB devices during boot and while using DOS.

Auto This option auto detects USB Keyboards or Mice and if found, allows them to be utilized during boot and while using DOS.

Port 64/60 Emulation

It uses USB to receive the IO port 64/60 trap to emulate the legacy keyboard controller.

USB 2.0 Controller Mode

The USB 2.0 Controller Mode configures the data rate of the USB port. The options are **FullSpeed (12 Mbps)** and **HiSpeed (480 Mbps)**.

7.4 PCI/PnP Setup

Select the PCI/PnP tab from the setup screen to enter the Plug and Play BIOS Setup screen. You can display a Plug and Play BIOS Setup option by highlighting it using the < Arrow > keys. The Plug and Play BIOS Setup screen is shown below.

BIOS SETUP UTILITY						
Main	Advanced	PCIPnP	Boot	Security	Chipset	Exit
Advanced PCI/PnP Settings						
WARNING: Setting wrong values in below sections may cause system to malfunction.						
IRQ3	[Available]					Available: Specified IRQ is available to be used by PCI/PnP devices. Reserved: Specified IRQ is reserved for use by Legacy ISA devices. ← Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
IRQ4	[Available]					
IRQ5	[Available]					
IRQ7	[Available]					
IRQ9	[Available]					
IRQ10	[Available]					
IRQ11	[Available]					
IRQ14	[Available]					
IRQ15	[Available]					
DMA Channel 0	[Available]					
DMA Channel 1	[Available]					
DMA Channel 3	[Available]					
DMA Channel 5	[Available]					

v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.

IRQ

Set this value to allow the IRQ settings to be modified. **Available** – This setting allows the specified IRQ to be used by a PCI/PnP device. **Reserved** – This setting allows the specified IRQ to be used by a legacy ISA device.

DMA Channel

Set this value to allow the MDA settings to be modified. **Available** – This setting allows the specified DMA to be used by a PCI/PnP


device. **Reserved** – This setting allows the specified DMA to be used by a legacy ISA device.

7.5 Boot Setup

Select the Boot tab from the setup screen to enter the Boot BIOS Setup screen. You can select any of the items in the left frame of the screen, such as Boot Device Priority, to go to the sub menu for that item. You can display a Boot BIOS Setup option by highlighting it using the < Arrow > keys. Select an item on the Boot Setup screen to access the sub menu for:


- ▶ Boot Settings Configuration
- ▶ Boot Device Priority
- ▶ Removable Devices

The Boot Settings screen is shown below:



Boot Setting Configuration

Use this screen to select options for the Boot Settings Configuration. Use the up and down <Arrow> keys to select an item. Use the <Plus> and <Minus> keys to change the value of the selected option. The settings are described on the following pages. The screen is shown below.



Quick Boot

Disabled – Set this value to allow the BIOS to perform all POST tests. **Enabled** – Set this value to allow the BIOS to skip certain POST tests to boot faster.


Boot Device Priority

BIOS SETUP UTILITY	
Boot	
Boot Device Priority 1st Boot Device [USB:Generic STORAGE]	Specifies the boot sequence from the available devices. A device enclosed in parenthesis has been disabled in the corresponding type menu.
Options USB:Generic STORAGE DEVICE Disabled	+ Select Screen ↑↓ Select Item +- Change Option F1 General Help F10 Save and Exit ESC Exit
v02.61 (C) Copyright 1985-2006, American Megatrends, Inc.	

Boot Devices Priority

This specifies the boot sequence from the available devices.
 The 1st Boot Device is primary device.

Removable Drives



Removable Drives

This specifies the Boot Device Priority sequence from available Removable Drives. Disabled – Set this menu to allow the BIOS to remove device on Boot Device Priority. Device name – Set this menu to allow the BIOS to stay device on Boot Device Priority

Remember the Password

Keep a record of the new password when the password is changed. If you forget the password, you must erase the system configuration information in NVRAM.

To access the sub menu for the following items, select the item and press < Enter >:

- ▶ Change Supervisor Password
- ▶ Change User Password
- ▶ Clear User Password

Supervisor Password

Indicates whether a supervisor password has been set.

User Password

Indicates whether a user password has been set.

Change Supervisor Password

Select this option and press < Enter > to access the sub menu. You can use the sub menu to change the supervisor password.

Change User Password

Select this option and press < Enter > to access the sub menu. You can use the sub menu to change the user password.

Clear User Password

Select this option and press < Enter > to access the sub menu. You can use the sub menu to clear the user password.

Change Supervisor Password

Select Change Supervisor Password from the Security Setup menu and press < Enter >.

Enter New Password:

Type the password and press < Enter >. The screen does not display the characters entered. Retype the password as prompted and press < Enter >. If the password confirmation is incorrect, an error message appears. The password is stored in NVRAM after completes.

Change User Password

Select Change User Password from the Security Setup menu and press < Enter >.

Enter New Password:

Type the password and press < Enter >. The screen does not display the characters entered. Retype the password as prompted and press < Enter >. If the password confirmation is incorrect, an error message appears. The password is stored in NVRAM after completes.


7.7 Chipset Setup

Select the Chipset tab from the setup screen to enter the Chipset BIOS Setup screen. You can select any of the items in the left frame of the screen, such as CPU Configuration, to go to the sub menu for that item. You can display a Chipset BIOS Setup option by highlighting it using the < Arrow > keys. The Chipset BIOS Setup screen is shown below.



South Bridge Configuration

You can use this screen to select options for the South Bridge Configuration. South Bridge is a chipset on the motherboard that controls the basic I/O functions, USB ports, audio functions, modem functions, IDE channels, and PCI slots. Use the up and down < Arrow > keys to select an item. Use the < Plus > and < Minus > keys to change the value of the selected option.



82571EB PCIE connect to

Set the onboard LAN to connect to either J2/RTM or Front I/O. The settings are **RTM** (J2) and **GigaLAN** (Front I/O).

Onboard LAN Boot ROM control


Set this value to enable/disable the LAN Controller PXE function. The PXE function allows system boot from a network environment.

Onboard VGA

You can use this option to control the onboard VGA. The settings are **Enabled** and **Disabled**.

7.8 Exit Menu

Select the Exit tab from the setup screen to enter the Exit BIOS Setup screen. You can display an Exit BIOS Setup option by highlighting it using the < Arrow > keys. The Exit BIOS Setup screen is shown below.



Save Changes and Exit

When you have completed the system configuration changes, select this option to leave Setup and reboot the computer so the new system configuration parameters can take effect.

Save Configuration Changes and Exit Now?

[Ok] [Cancel]

appears in the window. Select Ok to save changes and exit.

Discard Changes and Exit

Select this option to quit Setup without making any permanent changes to the system configuration.

Discard Changes and Exit Setup Now?

[Ok] [Cancel]

appears in the window. Select Ok to discard changes and exit.

Discard Changes

Select Discard Changes from the Exit menu and press < Enter >.

Select Ok to discard changes.

Load Optimal Defaults

Automatically sets all Setup options to a complete set of default settings when you select this option. The Optimal settings are designed for maximum system performance, but may not work best for all computer applications. In particular, do not use the Optimal Setup options if your computer is experiencing system configuration problems.

^{This page intentionally left blank.}
Select Load Optimal Defaults from the Exit menu and press < Enter >.

Select Ok to load optimal defaults.

Load Failsafe Defaults

Automatically sets all Setup options to a complete set of default settings when you select this option. The Failsafe settings are designed for maximum system stability, but not maximum performance. Select the FailSafe Setup options if your computer is experiencing system configuration problems.

Select Load Fail-Safe Defaults from the Exit menu and press < Enter >.

Load FailSafe Defaults?

[Ok] [Cancel]

appears in the window. Select Ok to load FailSafe defaults.

Important Safety Instructions

Please read and follow all instructions marked on the product and in the documentation before operating the system. Retain all safety and operating instructions for future use.

- ▶ Please read these safety instructions carefully.
- ▶ Please keep this User's Manual for future reference.
- ▶ The equipment should be operated within the recommended operating temperature.
- ▶ The equipment should be operated only from the type of power source indicated on the rating label. Make sure the voltage of the power source is correct when connecting the equipment to the power outlet.
- ▶ If the user's equipment has a voltage selector switch, make sure that the switch is set to the proper position for the area. The voltage selector switch is set at the factory to the correct voltage.
- ▶ For pluggable equipment, ensure they are installed near a socket-outlet that is easily accessible.
- ▶ Secure the power cord to prevent unnecessary accidents. Do not place anything over the power cord.
- ▶ If the equipment will not be in use for long periods of time, disconnect the equipment from mains to avoid being damaged by transient overvoltage.
- ▶ All cautions and warnings on the equipment should be noted.
- ▶ Please keep this equipment away from humidity.
- ▶ Do not use this equipment near water or a heat source.
- ▶ Place this equipment on a reliable surface when installing. A drop or fall could cause injury.
- ▶ Never pour any liquid into the opening, this could cause fire or electrical shock.

- ▶ Openings in the case are provided for ventilation. Do not block or cover these openings. Make sure there is adequate space around the system for ventilation when setting up the work area. Never insert objects of any kind into the ventilation openings.
- ▶ To avoid electrical shock, always unplug all power and modem cables from the wall outlets before removing covers.
- ▶ Lithium Battery provided (real time clock battery)

“CAUTION - Risk of explosion if battery is replaced by an incorrect type. Dispose used batteries as instructed in the instructions”

- ▶ The equipment should be checked by service personnel if one of the following situation arises:
 - ▷ The power cord or plug is damaged.
 - ▷ Liquid has penetrated the equipment.
 - ▷ The equipment has been exposed to moisture.
 - ▷ The equipment is not functioning or does not function according to the user's manual.
 - ▷ The equipment has been dropped and damaged.
 - ▷ If the equipment has obvious sign of breakage.
- ▶ Never open the equipment. For safety reasons, the equipment should only be opened by qualified service personnel.

Getting Service

Contact us should you require any service or assistance.

ADLINK Technology, Inc.

Address: 9F, No.166 Jian Yi Road, Chungho City,
Taipei County 235, Taiwan

台北縣中和市建一路 166 號 9 樓

Tel: +886-2-8226-5877

Fax: +886-2-8226-5717

Email: service@adlinktech.com

Ampro ADLINK Technology, Inc.

Address: 5215 Hellyer Avenue, #110, San Jose, CA 95138, USA

Tel: +1-408-360-0200

Toll Free: +1-800-966-5200 (USA only)

Fax: +1-408-360-0222

Email: info@adlinktech.com

ADLINK Technology (China) Co., Ltd.

Address: 上海市浦东新区张江高科技园区芳春路 300 号 (201203)

300 Fang Chun Rd., Zhangjiang Hi-Tech Park,
Pudong New Area, Shanghai, 201203 China

Tel: +86-21-5132-8988

Fax: +86-21-5132-3588

Email: market@adlinktech.com

ADLINK Technology Beijing

Address: 北京市海淀区上地东路 1 号盈创动力大厦 E 座 801 室(100085)

Rm. 801, Power Creative E, No. 1, B/D

Shang Di East Rd., Beijing, 100085 China

Tel: +86-10-5885-8666

Fax: +86-10-5885-8625

Email: market@adlinktech.com

ADLINK Technology Shenzhen

Address: 深圳市南山区科技园南区高新南七道 数字技术园

A1 栋 2 楼 C 区 (518057)

2F, C Block, Bldg. A1, Cyber-Tech Zone, Gao Xin Ave. Sec. 7,
High-Tech Industrial Park S., Shenzhen, 518054 China

Tel: +86-755-2643-4858

Fax: +86-755-2664-6353

Email: market@adlinktech.com

ADLINK Technology (Europe) GmbH

Address: Nord Carree 3, 40477 Duesseldorf, Germany

Tel: +49-211-495-5552

Fax: +49-211-495-5557

Email: emea@adlinktech.com

ADLINK Technology, Inc. (French Liaison Office)

Address: 15 rue Emile Baudot, 91300 Massy CEDEX, France

Tel: +33 (0) 1 60 12 35 66

Fax: +33 (0) 1 60 12 35 66

Email: france@adlinktech.com

ADLINK Technology Japan Corporation

Address: 151-0072 東京都渋谷区幡ヶ谷

1-1-2 朝日生命幡ヶ谷ビル 8F

Asahiseimei Hatagaya Bldg. 8F

1-1-2 Hatagaya, Shibuya-ku, Tokyo 151-0072, Japan

Tel: +81-3-4455-3722

Fax: +81-3-5333-6040

Email: japan@adlinktech.com

ADLINK Technology, Inc. (Korean Liaison Office)

Address: 서울시 서초구 서초동 1506-25 한도 B/D 2 층

2F, Hando B/D, 1506-25, Seocho-Dong, Seocho-Gu,

Seoul 137-070, Korea

Tel: +82-2-2057-0565

Fax: +82-2-2057-0563

Email: korea@adlinktech.com

ADLINK Technology Singapore Pte. Ltd.

Address: 84 Genting Lane #07-02A, Cityneon Design Centre,

Singapore 349584

Tel: +65-6844-2261

Fax: +65-6844-2263

Email: singapore@adlinktech.com

ADLINK Technology Singapore Pte. Ltd. (Indian Liaison Office)

Address: No. 1357, "Anupama", Sri Aurobindo Marg, 9th Cross,

JP Nagar Phase I, Bangalore - 560078, India

Tel: +91-80-65605817

Fax: +91-80-22443548

Email: india@adlinktech.com